

## AGREEMENT TO PURCHASE CUSTOM AMBULANCES

This Agreement to Purchase Custom Ambulances (“Agreement”) is made and entered into as of \_\_\_\_\_ (“Effective Date”) by and between the City of North Las Vegas, a Nevada municipal corporation (“City”) and Braun Industries, Inc. an Ohio corporation (“Provider”).

### RECITALS

WHEREAS, the City desires to purchase three (3) 2025 Chief XL Type 1 Ford F550 Gas Chassis Ambulances (“Products”) for its Fire Department, as more particularly described in Provider’s quote dated December 31, 2024 (“Quote”); attached hereto as **Exhibit A**.

WHEREAS, the City desires to purchase the Products from Provider as outlined in this Agreement, and Provider agrees to sell and deliver the Products upon the terms and conditions described in this Agreement.

**NOW, THEREFORE**, upon good and valuable consideration, the receipt and sufficiency of which is hereby acknowledged, the City and the Provider agree to the following terms, conditions and covenants:

### SECTION ONE RESPONSIBILITY OF PROVIDER

1.1. The Provider shall perform all of its obligations in the manner set forth in this Agreement including, without limitation, selling the Products to the City at the prices and quantities set forth in the Provider’s Quote, and all related additional or incidental tasks necessary to effectuate the intent of this Agreement.

1.2. The Products shall be new and must meet or exceed the technical specifications detailed in the Quote or as otherwise specified by the City.

1.3. The Provider shall ship the Products to a shipping address specified by the City (“Delivery Location”) F.O.B. Delivery Location as ordered by the City. Provider bears all risk of loss or damage to the Products until delivery of the Products to the City. Title to the Products passes to the City only after delivery and unloading of the Products at the Delivery Location is complete. Delivery of the Products is not complete until such Products have physically been received and accepted by the City.

1.4. The Provider shall furnish all user, instruction, or operator manuals for the Products as applicable.

1.5. The Provider shall furnish copies of all standard product warranties, extended warranties, and service and maintenance agreements for the Products from any manufacturer. To the extent possible, the Provider shall transfer or assign such warranties and agreements upon the request of the City.

1.6. The Provider shall promptly notify the City any time that the Provider fails to meet the requirements of this Agreement and shall, at its own expense, promptly take all actions to come back into compliance with this Agreement. If the Provider performs any additional task without obtaining the City's prior written approval, the Provider does so at its own risk and expense.

1.7. The Provider shall at its own expense comply at all times with all municipal, county, state and federal laws, regulations, rules, codes, ordinances and other applicable legal requirements.

## **SECTION TWO PAYMENT AND TERM**

2.1. The term of this Agreement shall commence on the Effective Date and continue until the Products are received, inspected, and accepted by the City ("Term"). The price per vehicle shall be Four Hundred Seven Thousand, Nine Hundred Seventy-Six Dollars and 00/100 (\$407,976.00) for a total contract amount of One Million, Two Hundred Twenty-Three Thousand, Nine Hundred Twenty-Eight Dollars and 00/100 (\$1,223,928.00).

2.2. The price per vehicle detailed in Section 2.1 of this Agreement will remain in effect for the Term. No additional compensation shall be paid, and no increase in the time of performance shall be awarded to the Provider without the prior written authorization of the City to proceed with such changes.

2.3. Payment to the Provider shall be made within thirty (30) calendar days after the City receives each invoice from the Provider, provided that such invoice is complete, correct, and undisputed by the City. Upon reconciliation of all errors, corrections, credits, and disputes, payment to the Provider will be paid in full within 30 calendar days. Invoices received without a valid purchase order number will be returned unpaid. The Provider shall submit the original invoice via email to:

AccountsPayable@CityofNorthLasVegas.com

## **SECTION THREE REPRESENTATIONS AND WARRANTIES**

3.1. Provider represents and warrants for the benefit of City, in addition to any other representations and warranties made in this Agreement, with the knowledge and expectation of City's reliance thereon, as follows:

3.1.1. Provider is a duly formed and validly existing corporation and is in good standing pursuant to the laws of the State of Nevada and has the full power, authority and legal right to execute, deliver and perform under this Agreement.

3.1.2. The Products are now and shall be at the time of delivery free from any security interest, lien, or other encumbrance.

3.1.3. Provider is financially solvent, able to pay its debts as they mature, and possessed of sufficient working capital to perform all of its obligations under this Agreement.

3.2. The representations and warranties made by Provider survive the termination or expiration of the Agreement.

#### **SECTION FOUR INSURANCE**

Provider shall obtain and maintain, at its expense, the following insurance coverage for all work related to the performance of this Purchase Agreement: commercial general liability insurance, automobile liability insurance, worker's compensation insurance, and employers' liability insurance. While a copy of the Provider's insurance certificate is not immediately required, the City reserves the right to request a copy of the Provider's insurance certificate at any time during the Term of the Agreement. It is the Provider's responsibility to produce the insurance certificate upon the City's request.

#### **SECTION FIVE TERMINATION**

Per agreed terms and conditions included in Exhibit A.

#### **SECTION SIX INDEMNIFICATION**

Notwithstanding any of the insurance requirements or limits of liability set forth herein, the Provider shall defend, protect, indemnify and hold harmless the City, and its officers, agents and employees, from any liabilities, claims, damages, losses, expenses, proceedings, suits, actions, decrees, judgments, reasonable attorneys' fees, and court costs which the City suffers, and/or its officers, agents or employees suffer, as a result of, or arising out of, the negligent or intentional acts or omissions of the Provider, its agents, and employees, or anyone employed by any of them, in fulfillment or performance of the terms, conditions or covenants of this Agreement. This Section 6 shall survive the termination or expiration of this Agreement until such time as the applicable statutes of limitation expire.

#### **SECTION SEVEN NOTICES**

7.1. All notices, demands and other instruments required or permitted to be given pursuant to this Agreement shall be in writing and be deemed effective upon delivery in writing if served by email, personal delivery, by overnight courier service, by facsimile or by overnight express mail, or upon posting if sent by registered or certified mail, postage prepaid, return receipt requested, and addressed as follows:

///

To City: City of North Las Vegas  
Attention: Belia Guzman  
2250 Las Vegas Blvd., North, Suite 820  
North Las Vegas, NV 89030  
Phone: 702-633- 1464

To Provider: Braun Industries, Inc.  
Attention: David Greenfeld  
1170 Production Dr.  
Van Wert, OH  
Phone: 419-203-6544

7.2. The address to which any notice, demand or other writing may be delivered to any party as above provided may be changed by written notice given by such party as above provided.

## **SECTION EIGHT SAFETY**

8.1. Obligation to Comply with Applicable Safety Rules and Standards. Provider shall ensure that it is familiar with all applicable safety and health standards promulgated by state and federal governmental authorities including, but not limited to, all applicable requirements of the Occupational Safety and Health Act of 1970, including all applicable standards published in 29 C.F.R. parts 1910, and 1926 and applicable occupational safety and health standards promulgated under the state of Nevada. Provider further recognizes that, while Provider is performing any work on behalf the City, under the terms of this Agreement, Provider agrees that it has the sole and exclusive responsibility to assure that its employees and the employees of its subcontractors comply at all times with all applicable safety and health standards as above-described and all applicable City safety and health rules.

8.2. Safety Equipment. Provider will supply all of its employees and subcontractors with the appropriate Safety equipment required for performing functions at the City facilities.

## **SECTION NINE MISCELLANEOUS**

9.1. Nevada and City Law. The laws of the State of Nevada and the North Las Vegas Municipal Code shall govern the validity, construction, performance and effect of this Agreement, without regard to conflicts of law. The parties to this Agreement consent to the jurisdiction of any court of competent jurisdiction in Clark County, Nevada to adjudicate any dispute related top this Agreement or actions to enforce or interpret the terms of this Agreement.

9.2. Assignment. Any attempt to assign this Agreement by the Provider without the prior written consent of the City shall be void.

///

9.3. Non-Waiver. The failure to enforce or the delay in enforcement of any provision of this Agreement by a party shall in no way be construed to be a waiver of such provision or right unless such party expressly waives such provision or right in writing.

9.4. Partial Invalidity. If any term of this Agreement should be held by a court of competent jurisdiction to be invalid, void or unenforceable, all provisions not held invalid, void or unenforceable, shall continue in full force and effect.

9.5. Controlling Agreement. To the extent any of the terms or provisions in the Quote conflict with this Agreement, the terms and provisions of this Agreement shall govern and control. Any additional, different or conflicting terms or provisions contained in Provider's Quote or any other written or oral communication from Provider shall not be binding in any way on the City whether or not such terms would materially alter this Agreement, and the City hereby objects thereto.

9.6. Attorneys' Fees. In the event any action is commenced by either party against the other in connection with this Agreement, the prevailing party shall be entitled to its costs and expenses, including reasonable attorneys' fees, as determined by the court, including without limitation, fees for the services of the City Attorney's Office. This Section 9.6 shall survive the completion of this Agreement until the applicable statutes of limitation expire.

9.7. Entire Agreement. This Agreement constitutes the entire agreement between the parties and supersedes all prior representations, agreements and understandings of the parties. No addition to or modification of this Agreement shall be binding unless executed in writing by the parties hereto.

9.8. Time of Essence. Time is of the essence in the performance of this Agreement.

9.9. Shipping. The Products are to be packaged in a manner that assures they are protected against deterioration and contamination. All shipments are to meet applicable D.O.T. Regulations. Serial numbers noted on the packing slip must match the serial number of the actual goods shipped. Incorrect or questionable documentation of serial numbers may result in shipment rejection. Shipments rejected due to Provider error will be returned solely at Provider's cost.

9.10. Inspection. An authorized representative of the City will inspect the Products at time of delivery. If deficiencies are detected, the Products may be rejected and the Provider will be required to make necessary repairs, corrections, or replacements. Payment and/or commencement of a discount period will not be made until the corrective action is made, the Products are re-inspected and accepted.

9.11. Further Assurances. The Provider shall execute and deliver all such documents and perform such acts as are reasonably requested by the City to complete its obligations under this Agreement.

///

9.12. Effect of Agreement Termination. In the event this Agreement is terminated, all rights and obligations of the parties hereunder shall cease, other than indemnity obligations and matters that by their terms survive the termination hereof.

9.13. Fiscal Funding Out. The City reasonably believes that sufficient funds can be obtained to make all payments during the term of this Agreement. Pursuant to NRS Chapter 354, if the City does not allocate funds to continue the function performed by the Provider under this Agreement, this Agreement will be terminated when appropriated funds expire.

9.14. Public Record. Pursuant to NRS 239.010 and other applicable legal authority, each and every document provided to the City may be a "Public Record" open to inspection and copying by any person, except for those documents otherwise declared by law to be confidential. The City shall not be liable in any way to the Provider for the disclosure of any public record, including but not limited to documents provided to the City by the Provider. In the event the City is required to defend an action with regard to a public records request for documents submitted by the Provider, the Provider agrees to indemnify, hold harmless, and defend the City from all damages, costs, and expenses, including court costs and reasonable attorney's fees related to such public records request. This section 8.14 shall survive the expiration or early termination of the Agreement.

9.15. Electronic Signatures. For purposes of this Agreement, the use of facsimile, email or other electronic medium shall have the same force and effect as original signatures.

9.16. Federal Funding. Supplier certifies that neither it nor its principals are presently debarred, suspended, proposed for debarment, declared ineligible, in receipt of a notice of proposed debarment or voluntarily excluded from participation in this transaction by any federal department or agency. This certification is made pursuant to the regulations implementing Executive Order 12549, Debarment and Suspension, 28 C.F.R. pt. 67, § 67.510, as published as pt. VII of the May 26, 1988, Federal Register (pp. 19160-19211), and any relevant program specific regulations. This provision shall be required of every subcontractor receiving any payment in whole or in part from federal funds.

9.17. Boycott of Israel. Pursuant to NRS 332.065(4), Provider certifies that the Provider is not currently engaged in a boycott of Israel, and Provider agrees not to engage in a boycott of Israel during the Term.


[The remainder of page is intentionally left blank. Signature page to follow.]

**IN WITNESS WHEREOF**, the City and the Provider have caused this Agreement to be executed as of the day and year first above written.

City of North Las Vegas,  
a Nevada municipal corporation

Braun Industries, Inc.,  
an Ohio corporation

By: \_\_\_\_\_  
Pamela A. Goynes-Brown, Mayor

By:   
Title: President  
Name: Kim Braun

Attest:

By: \_\_\_\_\_  
Jackie Rodgers, City Clerk

Approved as to Form:

By: \_\_\_\_\_  
Andy Moore, City Attorney

Exhibit A

Quote

Please see attached page(s).





## Quotation Summary

North Las Vegas Chief XL 2025 1 Braun Proposals 2024-12-31 09-21-52

**Reference:** QUO0000011217 **Rev:** 1  
**Purchaser:** Braun  
**Contact:** Sales Administration  
**Address:** 1170 Production Dr.  
Van Wert, OH

**Telephone:** 419-232-7020

**Opportunity:** North Las Vegas Fire Department 2025  
**Account:** North Las Vegas FD  
**Contact:** Scott Schuster  
**Billing Address:** 4040 Losee Road  
North Las Vegas, NV  
United States

**Currency:** USD  
**Quotation Date:** 2024-12-31  
**Quote Exp Date:** 2025-02-01

**Sales Contact:** David Greenfeld  
**Mobile:** 419-203-6544

**Factory Contact:** David Greenfeld  
**Mobile:** 419-203-6544

### Name

Chief XL Type I

### Specifications

-72" Headroom  
-169"L Full Seam Welded Module



Product	Description	Quantity	Unit Net	Total Net
CHFXLI	169" long x 96" wide module with 72" headroom.	3.00	407,976.00	1,223,928.00

Dealer Net Amount Per Unit

407,976.00

**\*\* Product quotes are valid for 30 calendar days. After 30 calendar days quotes are subject to change. Any applicable discounts will be added and validated at time of invoice. Discounts subject to change.**

### Payment Terms:

**FORCE MAJEURE** "Company shall not be liable or responsible to Purchaser, or be deemed to have defaulted or breached these Standard Terms and Conditions, for any failure or delay in fulfilling or performing any of these Standard Terms and Conditions when and to the extent such failure or delay is caused by or results from acts or circumstances beyond the reasonable control of Company including, without limitation, acts of God, flood, fire, earthquake, explosion, governmental actions, war, invasion or hostilities, terrorist threats or acts, riot or other civil unrest, national emergency, revolution, insurrection, epidemic/pandemic, telecommunication breakdown, power outage, lockouts, strikes or other labor disputes (whether or not relating to either party's workforce), restraints or delays affecting carriers, inability or delay in obtaining chassis from an original equipment manufacturer or other supplies of adequate or suitable components or materials at reasonable prices."





# BRAUN PERFORMANCE EXCELLENCE SYSTEM

## Purchase Agreement

**Braun Industries Inc. (herein the "Company")**  
1170 Production drive  
Van Wert OH 45891

### AUTHORIZED DEALER OR DIRECT CUSTOMER ("PURCHASER")

**Company** Braun  
**Contact** Sales Administration  
**Address** 1170 Production Dr.  
Van Wert, OH  
**Email**  
**Phone** 419-232-7020

### END USER / FINAL CUSTOMER

**Company** North Las Vegas FD  
**Contact** Scott Schuster  
**Address** 4040 Losee Road  
North Las Vegas, NV  
United States  
**Email** schusters@cityofnorthlasvegas.com  
**Phone(W)** 702-669-3343  
**Phone(M)**

Company is engaged in the production, modification, and sale of ambulances and other vehicles (herein the "**Product**"). Sales to any Purchaser of Product by Company shall be governed by these Standard Terms and Conditions of Sale ("**Standard Terms and Conditions**") and they shall be binding upon both the Purchaser and the Company.

### CONTROLLING TERMS AND CONDITIONS

These Standard Terms and Conditions will constitute the entire agreement between the Purchaser and the Company with respect to the sale of Product by Company to Purchaser, except for matters involving quantity, price, specifications, or delivery terms, which will be agreed to in the manner provided below. The submission of a purchase order to Company by Purchaser shall not be considered an offer to, or otherwise act in any way, to amend, modify, alter, or terminate these Standard Terms and Conditions. Without limiting the foregoing, (i) the provisions of these Standard Terms and Conditions shall control in the event of any conflicting or inconsistent terms and conditions in a purchase order to Company by Purchaser, and (ii) Purchaser agrees that Company will be selling Product to Purchaser based on and in reliance upon Purchaser's agreement that Purchaser assents to all of the terms and conditions set forth herein. Company's performance or shipment of Product shall not be deemed an acceptance of any provision of an offer, expression of acceptance, confirmation, or any other communication from Purchaser (including a purchase order to Company from Purchaser) which is different from, or inconsistent with, the terms and conditions of these Standard Terms and Conditions. Without limiting the foregoing, Company objects to and is not bound by any term or condition on or in Purchaser's offer, purchase order, expression of acceptance, confirmation or any other communication which is different from, inconsistent with, or in addition to these Standard Terms and Conditions and any such terms and conditions proposed by Purchaser are hereby expressly rejected. Stenographic and clerical errors

are subject to correction. No additions or modifications to these Standard Terms and Conditions shall be valid unless confirmed in writing by Company. Company is not bound to furnish its Product or services except in accordance with these Standard Terms and Conditions.

### GOVERNING LAW AND VENUE

Unless applicable federal, state or local law specifically dictates otherwise, any question concerning the validity or interpretation of these Standard Terms and Conditions, or of any of the rights or obligations of the parties hereunder, shall be governed, construed, and enforced in accordance with the laws of the State of Ohio. Any and all actions or proceedings, at law or in equity, to enforce or interpret the provisions of these Standard Terms and Conditions shall be litigated in courts having situs within the County of Van Wert, State of Ohio. EACH PARTY HERETO AGREES AND SUBMITS TO THE EXCLUSIVE JURISDICTION OF ANY LOCAL OR STATE COURT LOCATED WITHIN THE COUNTY OF VAN WERT, STATE OF OHIO, OR THE UNITED STATES FEDERAL DISTRICT COURT FOR THE NORTHERN DISTRICT OF OHIO (WESTERN DIVISION), FOR ANY DISPUTES ARISING HEREUNDER. Each party agrees that any service of process in such action or proceeding may be made by personal service upon such party wherever such party may be then located, or by certified or registered mail directed to such party at such party's last known address. Further, each Purchaser and Company irrevocably waives any immunity, defense, motion, and objection from the personal jurisdiction of any such court or from any legal process therein.

### ORDER TRANSMISSION and ACCEPTANCE

Purchaser may order Product from Company only through Company's electronic quote/order system ("**Quote/Order System**"). To be valid for processing and to receive a quote from Company, the Purchaser must include (i) the signed Standard Terms and Conditions, (ii) the Product order specifications ("**Order Specification**").

The Standard Terms and Conditions, the Order Specification, the Statement of Limited Warranty, and if applicable...the Liquidated Damages Agreement, the Customer Supplied Parts equipment checklist and any other document or agreement generated by the Company's Quote/Order System are collectively referred to herein as the "**Purchase Agreement**."

### ORDER SPECIFICATION

Purchaser may convert any quote within the Quote/Order System into an order to produce Product by the Company for the Purchaser. Product will be manufactured only per the Order Specification for the Product as outlined within the Quote/Order System. Drawings are for visual reference only; in the case of discrepancy between the Order Specification and the drawings, the Order Specification will govern.

Any change requested by Purchaser to the Order Specification (a "**Change Request**") must be approved by Company within the Quote/Order System. Approval of a Change Request is subject to the nature of the change, timing and availability of materials/labor, the disruption such change may have on Company's operations, and an equitable change to the Purchase Price. Company may, from time to time, make changes to the Order Specification without the consent of Purchaser provided that such changes do not materially affect the form or function of the Product.

Material furnished by the Purchaser for installation in the Product by Company (herein the "**Customer Supplied Parts**") must (i) be of new product (ii) be delivered to Company with complete installation instructions (iii) be delivered to Company by the date specified by Company and (iv) be individually identified/marked and accompanied by the Customer Supplied Parts



# BRAUN PERFORMANCE EXCELLENCE SYSTEM

## Purchase Agreement

equipment checklist when shipped to Company. Customer Supplied Parts not received timely will be deleted from the order. Company shall not be held responsible for Customer Supplied Parts material quality, nor operational performance in any way and Purchaser hereby agrees to indemnify and hold harmless Company and its successors and assignees from all liabilities, obligations, costs, losses, demands, actions, proceedings, claims, damages, and penalties (including, without limitation, all attorney fees) incurred or suffered by Company and arising out of or relating to any Customer Supplied Parts furnished by the Purchaser.

Material requested by the Purchaser for installation in the Product by Company at a time other than in the normal course of manufacture, will not delay the Product from being ready for delivery to Purchaser.

### PRICES

The price for the Product ("**Purchase Price**") shall be as reflected in and agreed to by the parties in the Purchase Agreement. Unless otherwise specified in the Purchase Agreement:

- (a) the portion of the Purchase Price attributable to the selected OEM chassis may differ from any estimate/quote provided to Purchaser by Company prior to Company's final receipt of the OEM's invoice.
- (b) If transportation charges are included in the Purchase Price, any changes in transportation charges shall be borne by Purchaser. Unless otherwise stated herein, Company shall not be responsible for switching, handling, loading, sorting, storage, demurrage, or any other transportation or peripheral charges.

All prices are quoted, and all amounts are payable in U.S. Dollars. If any tax, public charge, tariff, duty, or increase in such taxes or tariffs, is now, or shall be, assessed, levied, or imposed upon, or with respect to the sale of Product by Company to Purchaser or upon any sale, delivery, or other action taken under any validly accepted order for Product, or upon the export or import of such Product, or if any change shall be made in the custom house or railway classification of such Product or in existing freight rates applicable thereto, the burden of such charge or change shall be borne by the Purchaser.

### DELIVERY TIMES

Quoted lead times and delivery expectations by Company are approximate and are based upon market and production conditions at the time of Purchaser's order for Product from Company. Purchaser agrees that Company shall not be liable for any delay in or failure to have the Product available for shipment in accordance with quoted lead times if such delay or failure is due to Force Majeure, delays from the chassis OEM, changes to Order Specifications, or any other circumstances or cause beyond Company's control. Quoted lead times and delivery expectations are not guaranteed unless specified in writing and executed by Company ("**Liquidated Damages Agreement**") attached hereto and incorporated by reference in the Purchase Agreement. Quoted lead times will be extended for approved change orders, delays from the chassis OEM and Force Majeure.

### DELIVERY & INVOICING

Delivery occurs and risk of loss passes to Purchaser when Seller places the Product at the Delivery Point and at the disposal of Purchaser. In the event multiple Product is purchased, Company reserves the right to place the Product at the Delivery Point as each Product is ready.

Upon completion of production and quality inspection by Company and the Product is declared ready for delivery, an invoice will be promptly generated by Company and forwarded to the Purchaser with a copy provided to Company's third party financing partner if applicable.

### FINANCING

Purchaser will maintain a financing arrangement between Purchaser and a financial institution for the purpose of financing the purchase of Product from Company and facilitating the payment for these Products to Company. Financing arrangement must be of adequate credit limit to finance maximum number of Products that may be financed by Purchaser. Failure to maintain an adequate financing facility would result in payment being due immediately post invoice date. If Purchaser chooses a financing facility other than the Company's third party financing partner, financing support and incentives will not be available.

### PAYMENT

Payment via Company's third party financing partner... Company's third party financing partner shall pay the net invoice amount immediately and in full upon receipt of invoice or prior to shipment of Product (whichever first occurs) ("**Payment Due Date**"). All payments are payable in U.S. Dollars, shall be made by wire transfer, and will be net of all floorplan and program incentives available to Purchaser at time of invoice.

Payment via any means other than Company's third party financing partner... Purchaser shall pay the net invoice amount in full within five (5) business days from receipt of invoice or prior to shipment of Product (whichever first occurs) ("**Payment Due Date**"). All payments are payable in U.S. Dollars, shall be made by wire transfer or check.

Purchaser agrees to pay interest on all amounts not paid by the Payment Due Date at a rate of four percent (4%) per annum over the rate of interest last quoted by The Wall Street Journal as the "**Prime Rate**." If Company shall, in its sole discretion, deem itself to be insecure regarding Purchaser's ability to fulfill the terms of payment herein specified, whether due to Purchaser's financial condition or any other reason, Company may modify the credit terms herein, including full or partial payment in advance of delivery.

If any tax, public charge, tariff, duty, or increase in such taxes or tariffs, is now, or shall be, assessed, levied, or imposed upon, or with respect to the sale of Product by Company to Purchaser or upon any sale, delivery, or other action taken under the Purchase Agreement, or if any change shall be made in the custom house or railway classification of such Product or in existing freight rates applicable thereto, the burden of such charge or change shall be borne by the Purchaser.

### STATEMENT OF ORIGIN

As collateral security for the payment of the Purchase Price of the Product, Purchaser hereby grants to Company a lien on and security interest in and to all of the right, title, and interest of Purchaser in, to, and under the Product, wherever located, and whether now existing or hereafter arising or acquired from time to time, and in all accessions thereto and replacements or modifications thereof, as well as all proceeds, including insurance proceeds, of the foregoing. The security interest granted under this provision constitutes a purchase money security interest under the Ohio Uniform Commercial Code. Chassis Manufacturer's Statement of Origin shall pass to Purchaser after payment to Company and/or Company's third party financing partner has cleared the bank. Payment includes any interest and other related costs and expenses to Company or to the Company's third party financing partner.

### INSPECTION & ACCEPTANCE

Purchaser may inspect Product prior to shipment. Purchaser will be deemed to have accepted the Product unless it notifies Company in writing of any Nonconforming Product during the Fifteen (15) business days following the date of Delivery ("**Inspection Period**") and furnishes such written evidence or other documentation as may reasonably be required by the Company.



# BRAUN PERFORMANCE EXCELLENCE SYSTEM

## Purchase Agreement

**"Nonconforming Product"** means only the following: (i) Product shipped is different than identified in the applicable Purchase Agreement; (ii) the Product does not conform to the specifications listed in the applicable Order Specification, or (iii) on visual inspection, Purchaser reasonably determines that the Product is otherwise Defective. **"Defective"** means that the Product does not conform to the warranties set forth in the Statement of Limited Warranty. Nonconforming Product shall be held for Company inspection or disposition.

### SHIPMENT

Shipping terms are EXW Company's facility, specified in the applicable Order Specifications, Incoterms® 2020 (the **"Delivery Point"**). All claims for damages incurred during shipment, whether to person or property, shall be made by Purchaser directly to its Carrier, including any claims arising from the failure of the Carrier to comply with federal, state and local weight and/or size limitations. In the event that Company arranges for a Carrier to ship the Product to Purchaser, Purchaser acknowledges that such arrangement is for Purchaser's benefit and releases Company for any claims, whether to person or property, arising out of the loading or shipping of the Product sold. In the event multiple Product is purchased, Company reserves the right to make Product available in partial shipments.

Company shall not be liable for any direct, indirect, consequential, special, or incidental losses or damages resulting from its delay in shipment. The transfer of the risk of loss for damage and responsibility shall remain as described in this agreement, even in the event the Purchaser mandates Company to appoint a local driver or transportation company to deliver a Product from the Delivery Point to a drop shipment point mutually agreed upon, in order to facilitate the physical transfer of the Product.

If shipment is delayed by any cause other than by Company payment shall be due as if shipment had been made, storage shall be at the risk of Purchaser, and a daily fee of \$75 will be charged for extended storage and insurance after Fifteen (15) business days following the date of Delivery.

### INSURANCE

Prior to shipment, and unless the transfer of ownership to the Purchaser has been completed, Company shall be supplied with proof of insurance protecting against loss and physical damage to Product, naming Company as loss payee. Such insurance shall remain in full force and effect until such time as Company receives payment in full for the Product.

### NON-DELIVERY

The quantity of Product as recorded by Company upon dispatch from Company's place of business is conclusive evidence of the quantity of Product received by Purchaser upon delivery unless Purchaser can provide conclusive evidence proving the contrary. Company shall not be liable for any non-delivery of Products, even if caused by Company negligence, unless Purchaser gives written notice to Company of the non-delivery within 10 days of the date when the Product would in the ordinary course of events have been placed at the disposal of Purchaser at the Delivery Point. Any liability of Company for non-delivery of the Product shall be limited to replacing the Product within a reasonable time or adjusting the invoice respecting such Product to reflect the actual quantity delivered.

### CANCELLATION

Company may, in its sole discretion, and without liability or penalty, cancel this Product order if Company determines that Purchaser (i) fails to pay any amount due under the Purchase Agreement, (ii) has not otherwise performed or

complied with any of the terms and conditions of the Purchase Agreement, in whole or in part, or (iii) becomes insolvent, files a petition for bankruptcy, or commences or has commenced against it proceedings relating to bankruptcy, receivership, reorganization, or assignment for the benefit of creditors. Company's election to cancel Purchaser's Product order under such circumstances is in addition to, and not in lieu of, any other rights or remedies that Company may have at either law or equity or under these Standard Terms and Conditions and the Purchase Agreement.

Prior to commencement of engineering, any cancellation of Product order will incur a \$2,500 cancellation fee to the Purchaser. Once Company commences engineering, no cancellation of this Product order is permitted, and the full purchase price is due and payable to Company. Notwithstanding other provisions of this Agreement, and in addition thereto, Company shall be entitled to its reasonable and anticipated lost profit from such cancellation.

### FORCE MAJEURE

Company shall not be liable or responsible to Purchaser, or be deemed to have defaulted or breached these Standard Terms and Conditions, for any failure or delay in fulfilling or performing any of these Standard Terms and Conditions when and to the extent such failure or delay is caused by or results from acts or circumstances beyond the reasonable control of Company including, without limitation, acts of God, flood, fire, earthquake, explosion, governmental actions, war, invasion or hostilities, terrorist threats or acts, riot or other civil unrest, national emergency, revolution, insurrection, epidemic/pandemic, telecommunication breakdown, power outage, lockouts, strikes or other labor disputes (whether or not relating to either party's workforce), restraints or delays affecting carriers, inability or delay in obtaining chassis from an original equipment manufacturer or other supplies of adequate or suitable components or materials at reasonable prices.

### DEFAULT / ATTORNEY'S FEES

Purchaser is in default under the Purchase Agreement if any of the following occurs (except as prohibited by law): (i) Purchaser fails to perform any obligation that Purchaser has undertaken in the Purchase Agreement; (ii) Purchaser becomes insolvent, files a petition for bankruptcy, or commences or has commenced against it proceedings relating to bankruptcy, receivership, reorganization, or assignment for the benefit of creditors; or (iii) Company, in good faith, believes that Purchaser cannot, or will not, pay or perform the obligations it has agreed to fulfill under the Purchase Agreement.

If Purchaser defaults, or in the event Company brings an action or proceeding to enforce the terms hereof or declare rights hereunder, Purchaser agrees to pay Company costs for collecting amounts owing, including, without limitation, court costs, attorney's fees (for attorneys who are not our salaried employees), and fees for repossession, repair, storage, and sale of Product, all without relief from valuation and appraisal laws.

### REMEDIES

If Purchaser is in default under the Purchase Agreement: (i) Company shall have all the remedies provided under the terms of the Purchase Agreement and under law; (ii) Company may require Purchaser to immediately pay Company, subject to any refund required by law, the remaining unpaid balance due of the Purchase Price; (iii) Company may require Purchaser to make the Product available to Company at a designated place that is reasonably convenient to each party; (iv) Company may immediately take possession of the Product by legal process or self-help, but in doing so Company may not breach the peace or unlawfully enter onto Purchaser's premises; (v) Company may then sell the Product and apply what it receives as provided by law to Company's reasonable expenses and then toward Purchaser's obligations; and (vi) except



# BRAUN PERFORMANCE EXCELLENCE SYSTEM

## Purchase Agreement

when prohibited by law, Company may sue Purchaser for additional amounts if the proceeds of a sale do not pay all of the amounts Purchaser owes to Company. By choosing any one or more of these remedies, Company does not waive its right to use another remedy. Any waiver by Company of a breach of a term or condition of the Purchase Agreement shall not be construed as a waiver of any other breach of any other term or condition, or a waiver of any similar future breach of the same term or condition.

### CLAIMS

Purchaser must exercise diligence in inspection of the Product received from Company to mitigate damages in the event of repair or replacement of Defective or Nonconforming Product. Claims (except for claims required to be made in accordance with the provisions contained in the section of these Standard Terms and Conditions under the heading *"Shipment"*) must be made in writing to Company and Purchaser must give Company a reasonable opportunity to inspect the purported defect. If Product fails to conform to the applicable warranty given in the Statement of Limited Warranty, and if Purchaser has made a timely claim pursuant the terms of the Purchase Agreement including, without limitation, the Statement of Limited Warranty, then Company will honor the claim in the following manner: (i) Repairing the non-conforming part(s) of the Product; (ii) Replacing the non-conforming part(s) of the Product; or (iii) Issuing a return authorization and credit for the purchase price of the non-conforming Product. Such remedies shall represent and constitute the sole and exclusive remedy available to Purchaser for a breach of warranty (or other breach of contract) claim, tort claim (including negligence or strict liability), or any other claim with respect to the Product. The remedy shall be determined by Company in its sole and absolute discretion.

### COMPLIANCE WITH LAWS

Purchaser shall comply with all applicable law, regulations, and ordinances. Purchaser shall maintain in effect all the licenses, permission, authorizations, consents, and permits that it needs to carry out its obligations under the Purchase Agreement.

### NO WAIVER

The failure of Company upon knowledge of any default or violation by Purchaser of any of the provisions of the Purchase Agreement to enforce its rights or remedies shall not be construed as a waiver of such default or violation, or of any provision hereof, or of any rights or remedies Company may have at law or in equity.

### LIMITATION OF LITIGATION

Any controversy or claim of Purchaser arising out of or related to the Products and/or services provided hereunder must have accrued within the applicable warranty period, and then be commenced within 1-year after the cause of action has accrued.

### AMENDMENT AND MODIFICATION

The Purchase Agreement and any individual component thereof may only be amended or modified in writing and executed by an authorized representative of both the Purchaser and Company.

### ASSIGNMENT

Purchaser shall not assign any of its rights or delegate any of its obligations under the Purchase Agreement without the prior written consent of Company. Any purported assignment or delegation in violation of this Section is null and void. No assignment or delegation relieves Purchaser of any of its obligations under the Purchase Agreement.

### RELATIONSHIP OF THE PARTIES

The relationship between Purchaser and Company is that of independent contractors. Nothing contained in the Purchase Agreement shall be construed as creating any agency, partnership, joint venture, or other form of joint enterprise, employment, or fiduciary relationship between the parties, and neither party shall have authority to contract for or bind the other party in any manner whatsoever.

### NO THIRD-PARTY BENEFICIARIES

The Purchase Agreement is for the sole benefit of the parties hereto and their respective successors and permitted assigns, and nothing herein, express or implied, is intended to or shall confer upon any other person or entity any legal or equitable right, benefit, or remedy of any nature whatsoever under or by reason of the Purchase Agreement.

### LIMITATION OF LIABILITY

THE LIABILITY OF COMPANY ARISING OUT OF THE SUPPLYING OR SELLING OF THE PRODUCT, OR THEIR USE BY PURCHASER OR PURCHASER'S CUSTOMER, AND WHETHER BASED UNDER BREACH OF CONTRACT OR WARRANTY, IN TORT (INCLUDING NEGLIGENCE OR STRICT LIABILITY), OR OTHERWISE, SHALL NOT IN ANY EVENT EXCEED THE PURCHASE PRICE OF THE PRODUCT. THE REMEDIES SET FORTH ABOVE SHALL CONSTITUTE THE SOLE AND EXCLUSIVE REMEDY OF PURCHASER AND THE SOLE AND EXCLUSIVE LIABILITY OF COMPANY WHETHER THE CLAIMS OF PURCHASER ARE BASED ON CONTRACT, WARRANTY, TORT (INCLUDING NEGLIGENCE OR STRICT LIABILITY), OR OTHERWISE. UNDER NO CIRCUMSTANCES SHALL COMPANY BE LIABLE TO PURCHASER FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR PUNITIVE DAMAGES, WHETHER BASED UPON LOST GOODWILL, LOST RESALE PROFITS, WORK STOPPAGE, IMPAIRMENT OF OTHER PRODUCT, PROPERTY DAMAGE, LOSS OF FUSE, EXPENSES OF RECALL, OR OTHERWISE.

### ENTIRE AGREEMENT AND SEVERABILITY

Except as otherwise agreed in writing, the Purchase Agreement (which includes the Standard Terms and Conditions, the Order Specification, the Statement of Limited Warranty, and if applicable...the Liquidated Damages Agreement, the Customer Supplied Parts equipment checklist and any other document or agreement generated by the Company's Quote/Order System) constitute the entire agreement between Company and Purchaser, superseding all prior quotations and understandings, oral or written. All such previous communications are hereby abrogated and withdrawn, and no stipulations, representations, or agreements by Company or its officers, agents, or employees shall be binding upon Company unless reduced to writing and attached to and incorporated by reference herein, and no local, general, or trade custom shall alter or vary the terms hereof. If any provision hereof is determined invalid under applicable law, such invalidity shall be limited to such provisions without invalidating the remainder of the other provisions hereof.

### SURVIVAL

Provisions of the Purchase Agreement that by their nature should apply beyond their terms and shall remain in full force and effect after any termination or expiration of the Purchase Agreement including, but not limited to, the following provisions: Governing Law and Venue, Payment and Title, Insurance, Remedies, Claims, Compliance with Laws, No Waiver, Limitation of Litigation, Limitation of Liability, and Survival.

### SIGNATURE

The Purchase Agreement may be presented as an electronic record and accepted by an electronic signature, symbol, or process as permitted by the Ohio Uniform Electronic Transaction Act and the Federal Electronic Records and Signatures in Commerce Act, as applicable. An electronic signature of



# **BRAUN PERFORMANCE EXCELLENCE SYSTEM**

## **Purchase Agreement**

these Standard Terms and Conditions is considered a binding signature for the Purchase Agreement.



## BRAUN PERFORMANCE EXCELLENCE SYSTEM Purchase Agreement

**PURCHASER:**

City of North Las Vegas,  
a Nevada municipal corporation

**Pamela A. Goynes-Brown**

Print - Purchaser's Authorized Representative

Signature - Purchaser's Authorized Representative

**Mayor**

Title

Date

Attest:

By: \_\_\_\_\_

Jackie Rodgers, City Clerk

Approved as to form:

By: \_\_\_\_\_

Andy Moore, City Attorney

**BRAUN INDUSTRIES, INC:**

Purchase Order #:

Purchase Order Date:

Vehicle #:

Date Order Received \_\_\_\_\_

Date Order Specifications Approved by Purchaser for Release to  
Engineering \_\_\_\_\_

Braun. Authorized Representative (print)

Braun. Authorized Representative (signature)





## Quotation Summary

North Las Vegas Chief XL 2025 1 Braun Proposals 2024-12-31 09-21-52

**Reference:** QUO0000011217 **Rev:** 1

**Purchaser:** Braun

**Contact:** Sales Administration

**Address:** 1170 Production Dr.  
Van Wert, OH

**Telephone:** 419-232-7020

**Sales Contact:** David Greenfeld

**Mobile:**

**Phone:**

**Opportunity:** North Las Vegas Fire Department 2025

**Account:** North Las Vegas FD

**Contact:** Scott Schuster

**Billing Address:** 4040 Losee Road  
North Las Vegas, NV  
United States

**Currency:** USD

**Quotation Date:** 2024-12-26

**Quote Exp Date:** 2025-01-25

**Price Effective:** 2024-12-01

**Factory Contact:** Kris Turner

**Mobile:** 419-203-8639

### Name

Chief XL Type I

### Specifications

-72" Headroom

-169"L Full Seam Welded Module





## Sales Options by Category

### Braun - KKK Change Notice

Item Number	Description	Quantity
00-01-0001	GENERAL CONDITIONS	1.00
00-01-0006	DYNAMIC SIDE IMPACT & ROLLOVER TESTS	1.00
00-01-0017	BIDDER IS KKK-A-1822F AMENDMENT 1 COMPLIANT	1.00
80-11-0020	CAAS GVS 3.0 COMPLIANCE PACKAGE A CAAS GVS 3.0 compliance sticker, electrical load analysis sticker, and payload sticker shall be installed in the oxygen compartment. Any deviations from CAAS GVS 3.0 shall be listed in the vehicle delivery packet with a notation on the-compliance sticker.	1.00
00-01-0029	NO CONTRACT REQUIRED NO STS, HGAC, FSA, SOURCEWELL or GPO contract required	1.00
00-01-0053	NO BOND REQUIRED No Bond is Required	1.00

### Braun - Chassis

Item Number	Description	Quantity
SR00199000	Sierra Wireless Antenna on Cab Roof: Install a Customer Supplied Sierra Wireless antenna on the cab roof. The antenna shall terminate in the MCC.	1.00
SR00199001	A Federal EQ2B Electronic "Q" siren shall be installed, with a control head mounted in the master control console. IATS	1.00
SR00199003	FLOOR CONSOLE F450 CUSTOM CONSOLE - ALUMINUM: Build per the attached console layout.	1.00
SR00199007	SECONDARY COMPRESSOR: There is to be a secondary engine driven compressor installed on the chassis.	1.00
SR00199018	LABELS ON MCC-HEIGHT/LENGTH/WIDTH: There shall be a yellow label 5.5" x 2.5" yellow label with black lettering showing the overall Height, Length and Width in feet and inches applied to the MCC beneath the Vista, per attached photo.	1.00



SR00199040	----- <b>Relocate the controller for Liquid Spring in cab: Relocate the controller for the liquid spring to the inside of the dash panel, left of steering wheel. Reference photo attached.</b>	1.00
SR00199058	----- <b>SIREN SPEAKERS, - IN FRONT BUMPER: Install two (2) 100w siren speakers with cast housings in bumper. Install two (2)100w siren speakers behind grille area. Two to the standard siren and two to the EQ2B. Per dwg. #1.</b>	1.00
00-01-0040	----- <b>Administration Fee</b>	1.00
25XLF450-550	----- <b>TYPE I - AMBULANCE - CHIEF XL I FORD - 72 INCH INTERIOR HEADROOM</b> 2025 Chief XL Type I - 169" Module - 72" Interior Headroom. Manufactured in Van Wert, Ohio, USA.	1.00
CH_F2550LG	----- <b>CHASSIS - FORD F550 193" WB 4X2 DRW (108 C.A.) GAS ENGINE</b> FORD F550 GAS CHASSIS CAB, 193" WB 4X2 DRW (108" C.A.)	1.00
15-00-0010	----- <b>FUEL TANK - FULL UPON FACTORY RELEASE</b> The chassis fuel tank of the completed unit shall be full at time of release from the ambulance manufacturer's facility.	1.00
20-10-0603	----- <b>ENGINE BLOCK HEATER - OEM PLUG</b> An engine block heater shall be included in the chassis with the 125 VAC power cord.	1.00
20-20-0252	----- <b>HEAT SHIELDS, PROTECTIVE</b> Install: aluminized steel protective heat shields to the upper laterals above the exhaust system.	1.00
20-20-0277	----- <b>HIGH IDLE SYSTEM, AUTOMATIC</b> A high-idle module will be added to the chassis. The high idle will be engaged automatically by the M-Tech system when all chassis parameters are met. Chassis parameters include but not limited to vehicle in park, service brake not depressed, accelerator not depressed, parking brake set. High-idle is also activated by the M-Tech heat or A/C.	1.00
20-01-0105	----- <b>SUSPENSION - LIQUID SPRING TYPE I</b> Install: Liquid Spring	1.00
20-10-0206	----- <b>BATTERY - TWO SYSTEM - F SERIES CHASSIS</b> The vehicle shall have a 12 V two (2) battery system rated at 1500 cold cranking amps. Both batteries shall be securely installed in the Ford OEM locations, under the vehicle hood.	1.00
30-10-0012	----- <b>AIR HORNS - BUELL DUAL TRUMPETS 10" and 12", UNDR BMPR W/SW Standard location(s) unless otherwise specified.</b> Mount: Air Horn - (Buell) dual trumpets, (1) 10" and (1) 12" under/through front bumper (to accommodate chassis options), one each side, compressor with cover per drawing. Horns activated by a push button located on the MCC (master control console) unless otherwise stated. See Dwg #1	1.00



30-10-0030	<b>BACKUP ALARM</b> Install: (OSHA approved) back up alarm with a disable control for silent backing, located on the MCC (master control console). -----	1.00
20-30-0806	<b>RUNNING BOARDS - STAR PUNCHED DIAMOND PLATE</b> Aluminum diamond plate running boards with a star punched non-skid surface shall be provided on the cab. The running boards shall be dip anodized after they are formed to retain finish and increase corrosion resistance. -----	1.00
30-10-0757	<b>RUMBLER - FEDERAL SIGNAL SYSTEM / OPERATED VIA CONTROL SCREEN</b> Install a Federal Signal Rumbler system activated by the control screen. -----	1.00
20-30-0202	<b>MIRRORS, EXT OEM MANUAL TELESCOPING WREMOTE &amp; HEAT</b> The chassis shall have OEM manual telescoping, folding trailer tow mirrors with power/heated glass, heated convex spotter mirror, integrated clearance lamps/turn signals. -----	1.00
20-30-0261	<b>OEM AUTO-LOCK DISABLED (cab &amp; module doors do not auto lock or unlock)</b> The OEM auto-lock feature will be disabled. -----	1.00
30-10-0753	<b>SIREN, WHELEN 295-HFSA7-REMOTE WITH MICROPHONE (Meets CA Title 13)</b> A Whelen 295-HFSA7 remote dual siren amplifier shall be flush-mounted in the master control console located in the cab. The siren shall be capable of hands-free operation and shall be equipped with a noise canceling microphone. (Meets CA Title 13) -----	1.00
20-40-0203	<b>WHEELS, FORGED POLISHED ALUMINUM - 19.5 - F450/550 193" WB</b> Forged, polished aluminum wheels shall be provided, to include bright hub covers and center ornaments and valve stem extensions. -----	1.00

#### **Braun - Electrical**

<b>Item Number</b>	<b>Description</b>	<b>Quantity</b>
SR00199009	Indicator Light-Green A/C and Shoreline: Install two (2) green indicator lights, One (1) above the Shoreline and One (1) above the A/C plug ins on the streetside/front of module. -----	1.00
SR00199020	INVERTER, VANNER - 1100 WATT, LIFESINE LSC 12-1100-DC CHARGER switch-non-hardwired shall be installed in OSS #2. MODULE POWER TO COME ON WITH IGNITION. INVERTER TO COME ON WITH MODULE POWER. -----	1.00
SR00199034	Backup Camera Screen: Install freestanding backup camera screen constant on, no longer fed to V-Mux. -----	1.00
SR00199036	PRIMARY ACTION AREA WITH SUCTION CONTROL, 125VAC/12VDC/DUAL USB OUTLETS, OXYGEN OUTLET, DOMETIC CONTROL AND BYPASS, SCREEN ON AN ANGLED FLIP-DOWN PANEL	1.00



SR00199052	----- 12VDC-OUTLETS: One (1) installed in the primary action area. Located per dwg. #5. One (1) installed in the lower front wall cabinet #2. Located per dwg. #7. Both outlets are to be wired hot at all times.	1.00
SR00199078	----- POWER AND GROUND DROPS: Install a power and ground drop in OSS #2 and OSS #4. These are to be wired HOT at all times. The loop in OSS #2 is to be in the upper left hand corner of the compartment. The loop in OSS #4 is to be installed behind the closeout in OSS #4.	1.00
SR00199079	----- USB-DUAL OUTLET, TWO (2) INTERIOR Two (2) dual USB 5 volt 2.1 amp panel mount outlets (dual ports) shall be installed. The outlets shall have power and ground for charging equipment such as cell phones, iPad, etc... One (1) shall be installed in the primary action area located per dwg. #5 and one (1) shall be installed in the MCC located per the attached console layout. (Braun part #19277)	1.00
SR00199080	----- Pre-Wire for door opener/transponder: Braun to install a pre-wire in the front bumper for the door opener/transponder 12V 18 gauge ignition HOT wire to front bumper. Reference the attached photo for location.	1.00
SR00199081	----- RECEPTACLE SHORELINE INLET-TWO (2) SUPER AMP, AUTO EJECTS: Install two (2) Kussmaul 20 AMP super auto eject shoreline inlet receptacles with yellow covers on the module exterior (forward street side) near the driver's door. One (1) will be for the rooftop heat/ac and one (1) for the outlets, chargers, etc. Per dwg. #3.	1.00
SR00199082	----- SERVICE LOOP FOR ALL WARNING LIGHTS: Each warning light is to have a 4" to 6" service loop installed behind it.	1.00
SR00199084	----- DAVID CLARK SYSTEM: Install a three (3) position David Clark headset system. Two (2) positions are to be installed in the cab with headsets installed over the inside shoulder of each seated position as high as possible. The third position will be in the module located under the ACP door near the back of the left wall. All headsets will be H3432. The David Clark system will tie into a customer supplied/customer installed Motorola XTL 5000 radio.	1.00
SR00199088	----- OUTLETS, 125VAC - THREE (3) INTERIOR DUPLEX: Two (2) Installed in the primary action area. Located per dwg. #5. One (1) installed in the lower front wall cabinet #2. Located per dwg. #7.	1.00
SR00199089	----- RADIO ANTENNA BASES - TWO (2) Enter antenna information here: Two (2) antenna bases with attached coax cables shall be installed on the module roof. The coax cables shall terminate in the MCC. Access to the antenna bases shall be through adjacent module interior dome lights.	1.00



30-06-0001	<p>-----</p> <p><b>ELECTRICAL SYSTEM - MICRO PROCESSOR BASED</b></p> <p>Install: Microprocessor based multiplex system.</p> <p>-----</p>	1.00
30-10-0110	<p><b>ELECTRICAL CIRCUITS</b></p> <p>All electrical circuits: shall have wiring and circuit protection suitable to the demand and must meet the national electric code (NEC) wiring requirements, added on wiring (18 GA through 10 GA) color coded and stamped with code numbers for easy identification, SLX high temperature thermoplastic cross link wire used. SGX insulated cable used for all under hood / underbody battery and charging system cable. High temperature (375° f) thermoplastic loom used on all harnesses.</p> <p>-----</p>	1.00
30-06-0126	<p><b>ELECTRICAL COMPARTMENT (PDQ) - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Electrical compartment / hinged door w/ (2) chrome locking lever latches/ located on the partition wall behind the attendant seat.</p> <p>-----</p>	1.00
30-06-0325	<p><b>FLASHER - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Provide: Flasher within and programmed by the multiplex electrical system.</p> <p>-----</p>	1.00
30-06-0350	<p><b>FLASHING HEADLIGHTS - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Headlights (high beams) shall be programmed through the multiplex system to alternate flash (wig-wag).</p> <p>-----</p>	1.00
30-10-0190	<p><b>GROUND FAULT CIRCUIT INTERRUPTER-GFCI</b></p> <p>Install: A 125 VAC, 20 AMP circuit breaker with ground fault circuit interrupter (GFCI) electronic ground leakage detection in the load center for the shoreline circuit.</p> <p>-----</p>	1.00
30-06-0285	<p><b>MODULE DISCONNECT - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Install: Disconnect to keep the system power engaged after the ignition is switched to the "off" position.</p> <p>-----</p>	1.00
30-06-0575	<p><b>REVERSE -TRANSMISSION- FUNCTIONS - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>System programmed to provide activation for: rear outboard warning lights, rear side warning lights, rear scene lights, the rear side scene lights - when the transmission selector lever is placed into "reverse" position.</p> <p>-----</p>	1.00
30-06-0150	<p><b>SPARE CIRCUIT - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Provide (1) spare 15-amp circuit.</p> <p>-----</p>	1.00
30-06-0175	<p><b>WIRING HARNESS CONNECTORS - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Connect all wiring harnesses via quick connect circular plug connectors.</p> <p>-----</p>	1.00
30-06-0300	<p><b>VOLTMETER - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Provide: (1) digital voltmeter on the master control console screen.</p> <p>-----</p>	1.00
30-06-0026	<p><b>WARNING DISPLAY - MULTIPLEX ELECTRICAL SYSTEM</b></p> <p>Install: digital warning display integrated into the cab display console, programmed through the multiplex system to provide visual and audible indication.</p> <p>-----</p>	1.00
30-06-0225	<p><b>EMERGENCY MASTER SWITCH - MULTIPLEX ELECTRICAL SYSTEM</b></p>	1.00



Supply: A single emergency master switch for activating all the emergency warning lights on the master control console screen, emergency master switch will activate the module power automatically, include an Emergency Master Menu button to allow access to individual warning light functions.

<b>30-06-0250</b>	<b>CONTROL PANEL SWITCHES - MULTIPLEX ELECTRICAL SYSTEM</b> Switches on the master control console and attendant control panel screens shall have dimmable perimeter backlighting.	<b>1.00</b>
<b>30-06-0275</b>	<b>MODULE POWER SWITCH - MULTIPLEX ELECTRICAL SYSTEM</b> Provide: A module power switch for the electrical system on both the Master Control Console and the Attendant Control Panel screens.	<b>1.00</b>
<b>30-06-0101</b>	<b>ATTENDANT CONTROL PANEL (ACP) - MULTIPLEX ELECTRICAL SYSTEM</b> Attendant Control Panel (ACP) contains a color micro processor screen, controls all equipment installed in the patient compartment.	<b>1.00</b>
<b>30-06-0375</b>	<b>PARK OVERRIDE - MULTIPLEX ELECTRICAL SYSTEM</b> Park override switch on the master control console screen, reactivates all lights disabled when the transmission is placed in the neutral/park position.	<b>1.00</b>
<b>30-06-0400</b>	<b>LOAD MANAGER-SEQUENTIAL SWITCHING SYSTEM - MULTIPLEX ELECTRIC SYSTEM</b> Load manager-sequential switching system controlled by the microprocessor based electrical system: emergency master button shall control the sequential switching of the emergency lights and/or other warning devices, load manager shall automatically shed non-critical electrical loads during low voltage conditions.	<b>1.00</b>
<b>30-06-0450</b>	<b>FRONT CLEAR DISABLE SWITCH - MULTIPLEX ELECTRICAL SYSTEM</b> Activation of the switch on the master control console screen to disable all forward-facing clear warning lights.	<b>1.00</b>
<b>30-06-0076</b>	<b>MASTER CONTROL CONSOLE (MCC) - MULTIPLEX ELECTRICAL SYSTEM</b> Floor mounted Master Control Console (MCC) located in the cab, housing siren, color microprocessor display screen, controlling all the Emergency Warning functions, Patient Compartment lighting and module heat/ac functions.	<b>1.00</b>
<b>30-06-0475</b>	<b>CURBSIDE SCENE LIGHTS ON WITH CURBSIDE DOOR</b> The Curbside scene lights: programmed to activate when the Curbside door is in the open position.	<b>1.00</b>
<b>30-06-0500</b>	<b>REAR SCENE LIGHTS ON WITH REAR DOORS OPEN</b> Rear scene lights programmed to activate when the rear doors are in the open position.	<b>1.00</b>
<b>30-06-0525</b>	<b>DISABLE SWITCH FOR REAR SCENE LIGHTS - MULTIPLEX ELECTRICAL SYSTEM</b> Install: disable switch at the rear door area to disable the rear scene lights.	<b>1.00</b>
<b>30-06-0550</b>	<b>DISABLE SWITCH FOR SIDE SCENE LIGHTS - MULTIPLEX ELECTRICAL SYSTEM</b> A disable switch shall be installed at the curbside door area to disable the curbside scene lights.	<b>1.00</b>
<b>30-07-0001</b>	<b>CONTROL SCREEN, MCC</b>	<b>1.00</b>



	Install: interface module / display screen in the cab.	
<b>30-07-0003</b>	<b>CONTROL SCREEN, ACP</b> Install: interface module / display screen mounted on an angled flip - down panel with chrome lever latches, in the patient compartment ACP area.	1.00
<b>30-10-0901</b>	<b>SYSTEM ACTIVE AND CHECK OUT LIGHTS - 15 MINUTES</b> Switch: located at the curb and rear entry doors for activation of the electrical system, check out light switch located at the curb and rear doors for activation of the LED angled lights prior to entering the module, system programmed to shut down automatically after 15 minutes unless the ignition is on.	1.00
<b>30-06-0050</b>	<b>DAYTIME RUNNING LAMPS - MULTIPLEX ELECTRICAL SYSTEM</b> OEM Daytime Running Light headlights activated for daytime operation, when transmission is placed in drive.	1.00
<b>30-10-0068</b>	<b>CAMERA REAR VIEW - SINGLE SYSTEM - CONTROL SCREEN</b> Install: camera system rear view, tied to the control screen. Per Dwg #2. Camera alignment will be conducted at final inspection, if applicable.	1.00
<b>30-10-0079</b>	<b>CAMERAS, TWO (2) SIDE VIEW, STREETSIDE LEFT &amp; CURBSIDE RIGHT, 120 DEGREES ANGLE</b> Install (2) camera systems, street side exterior - left side view, and curb side exterior - right side view, Tied to M-Tech display screen.	1.00
<b>30-10-0299</b>	<b>LIGHT, ATTENDANT CONTROL PANEL AREA - TECNIQ SILHO-X LED - WARM WHITE</b> A Tecniq Silho-X 2.75" round warm white LED light with SS trim ring, shall be mounted above the left wall forward action area counter. The light shall be operated through a button on the control screen screen labeled "Attendant Light". (Braun #26415)	1.00
<b>30-10-0310</b>	<b>LIGHT, LED ELECTRICAL COMPARTMENT -PDQ</b> A 12 VDC LED light shall be located in the PDQ. The light shall be wired "battery-hot" to activate when the PDQ door is in the open position. The light shall be off when the door is in the closed position.	1.00
<b>30-11-0106</b>	<b>LIGHTS, DOME LED (8) WHELEN SUPER LED</b> Eight (8) Whelen #LED (80COEHCR) dome lights, shall be installed. See dwg #9	1.00
<b>30-11-0152</b>	<b>LIGHTS, RIDGEBACK LED PANEL (3) STREETSIDE - ANGLED</b> Install: (3) Ridgeback LED lights streetside per dwg #5.	1.00
<b>30-11-0176</b>	<b>LIGHTS, RIDGEBACK LED PANEL (2) CURBSIDE - ANGLED</b> Install: (2) Ridgeback LED lights mounted on an angled panel above curbside seating area per dwg #6.	1.00
<b>40-10-0151</b>	<b>SWITCH DOOR UNLOCK, WATERPROOF - HIDDEN IN FRONT GRILLE AREA</b> Install: exterior hidden door unlock switch in grille area.	1.00
<b>30-10-0926</b>	<b>SCENE LIGHT SENSOR TO SHUT OFF IN DAYLIGHT</b> Install: Dusk to Dawn photocell switch to turn off scene lighting during the daylight hours.	1.00
<b>30-06-0201</b>	<b>RADIO TIE-IN POINT - (1) 12V/40 AMP - CAB CONSOLE AREA</b>	1.00





	Install (1) set of 12 volt/40 amp radio tie-in studs in cab console: (1) battery hot, (1) ignition hot, (1) grounded stud.	
<b>30-06-0202</b>	<b>RADIO TIE-IN POINT - (1) 12V/40 AMP - PATIENT COMPARTMENT</b> Install (1) set of 12 volt/40 amp radio tie-in studs in patient compartment: (1) battery hot, (1) ignition hot, (1) grounded stud.	1.00
<b>30-06-0203</b>	<b>RADIO TIE-IN POINT - (1) 12V/250 AMP - PDQ</b> Install (1) set of 12 volt/250 amp radio tie-in studs in the PDQ: (1) battery hot, (1) ignition hot, (1) grounded stud.	1.00

### **Braun - Exterior Lighting**

<b>Item Number</b>	<b>Description</b>	<b>Quantity</b>
<b>SR00202816</b>	<b>Whelen Tail Light Housing. WHELEN M6 TAIL LIGHTS IN M6FCV3 CHROME HOUSING. See dwg #2.</b>	1.00
<b>SR00199019</b>	Each outside storage compartment equipped with Ridgeback LED strip lighting/located one each side of the door opening/activated by a magnetic switch/ all STD OSS door openings/does not include the battery compartment. Lengths dependent on OSS dimensions IPOS. OSS #2A and OSS #4C are to have a single strip of lights across the top of the compartment.	1.00
<b>SR00199027</b>	<b>CUSTOMER SUPPLIED GTT792AH OPTICOM: Install a customer supplied GTT792AH with bezel (Braun P/N 08895-1) . Opticom is to be located per dwg. #1.</b>	1.00
<b>SR00199028</b>	The (5) rear Whelen M7 warning lights should be red/blue. <b>LIGHTS, REAR MODULE - Whelen M7: Install five (5) M7 red/blue LED warning lights with clear lens. One (1) in the center and two (2) on each end, two (2) Whelen M7 LED load lights with chrome flanges, shall be installed on the rear of the module. The lights shall be installed with chrome flanges and shall be operated from switches on the master control console labeled "Flashers" and "Rear Scene Lights". Per dwg. #2. All lights are to have clear lens.</b>	1.00
<b>SR00199053</b>	<b>WARNING LIGHTS FLASH PATTERN RANDOM - MULTIPLEX ELECTRICAL SYSTEM: The default flash pattern for the vehicle warning lights shall be random.</b>	1.00
<b>SR00199065</b>	Install two (2) Whelen M6 red/blue LED warning lights with clear lenses, chrome flanges and waterproof connectors above the rear wheel wells, one (1) on each side. These lights shall operate from the master control console, labeled "Flashers", via the MasterTech Electrical System. NOTE: When the vehicle is placed in park, the override control must be on for intersection light(s) to remain on. Per dwg. #3 and #4.	1.00



SR00199066	Whelen strip lights shall be installed on the rub rail. Three (3) LED's each side, two (2) RED LED's and one (1) BLUE LED; alternating in color (red/blue/red) along the module side, for a total of six (6) lights. The LED lights shall alternate flash with box warning lights.	1.00
ClearLENS	CLEAR LENSES ON ALL WARNING LIGHTS	1.00
GWLIO0002	<b>LIGHTS GRILLE - 2 WHELEN ION LED</b> Two (2) Whelen ION series super LED warning lights, with waterproof connectors shall be installed the grille area of the chassis. The lights shall operate from a switch on the master control console labeled "Flashers". Note: these lights are only available with a clear lenses.	1.00
GWLC1R1RB	<b>GRILLE WARNING LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on the grille in location 1 shall be dual color red/blue.	1.00
GWLC1R2RB	<b>GRILLE WARNING LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on the grille in location 2 shall be dual color red/blue.	1.00
STRPTRN	<b>STRAIGHT PATTERN WARNING LIGHTS</b> The front warning lights will be aligned in a straight pattern across the module.	1.00
30-25-0122	<b>LIGHTS, ICC / LED CLEARANCE - ON MODULE FRONT - TECNIQ</b> Install: (5) amber Tecniq LED (S33-AA00-1) clearance / ICC lights on the front of the module near the roof line per dwg #1.	1.00
FWLM60007	<b>LIGHTS FRONT MODULE - 7 WHELEN M6 SUPER LED</b> Seven (7) Whelen M6 Super LED warning lights with chrome flanges shall be installed on the module front. The lights shall operate from a switch on the master control console labeled "Flashers".	1.00
FWLC1R1RB	<b>FRONT WARNING LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on the upper front of the module in location 1 shall be dual color red/blue.	1.00
FWLC1R2RB	<b>FRONT WARNING LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on the upper front of the module in location 2 shall be dual color red/blue.	1.00
FWLC1R3RB	<b>FRONT WARNING LIGHT LOCATION 3 - RED-BLUE</b> The warning light located on the upper front of the module in location 3 shall be blue.	1.00
FWLC1R4RB	<b>FRONT WARNING LIGHT LOCATION 4 - RED-BLUE</b> The warning light located on the upper front of the module in location 4 shall be dual color red/blue.	1.00
FWLC1R5RB	<b>FRONT WARNING LIGHT LOCATION 5 - RED-BLUE</b> The warning light located on the upper front of the module in location 5 shall be dual color red/blue.	1.00



<b>FWLCLR6RB</b>	<b>FRONT WARNING LIGHT LOCATION 6 - RED-BLUE</b> The warning light located on the upper front of the module in location 6 shall be dual color red/blue. -----	<b>1.00</b>
<b>FWLCLR7RB</b>	<b>FRONT WARNING LIGHT LOCATION 7 - RED-BLUE</b> The warning light located on the upper front of the module in location 7 shall be dual color red/blue. -----	<b>1.00</b>
<b>30-25-0123</b>	<b>LIGHTS, ICC / LED CLEARANCE - ON MODULE REAR - TECNIQ</b> Install: (5) red TECNIQ LED (S33-RR00-1) clearance / ICC lights on the rear of the module near the roof line per dwg #2. -----	<b>1.00</b>
<b>ROLCLR1RB</b>	<b>REAR OUTER MODULE LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on upper rear of the module, in outer location 1 shall be dual color red/blue. -----	<b>1.00</b>
<b>ROLCLR2RB</b>	<b>REAR OUTER MODULE LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on upper rear of the module, in outer location 2 shall be dual color red/blue. -----	<b>1.00</b>
<b>ROLCLR3RB</b>	<b>REAR OUTER MODULE LIGHT LOCATION 3 - RED-BLUE</b> The warning light located on upper rear of the module, in outer location 3 shall be dual color red/blue. -----	<b>1.00</b>
<b>ROLCLR4RB</b>	<b>REAR OUTER MODULE LIGHT LOCATION 4 - RED-BLUE</b> The warning light located on upper rear of the module, in outer location 4, shall be dual color red/blue. -----	<b>1.00</b>
<b>RCLCLR1RB</b>	<b>REAR CENTER MODULE LIGHT LOCATION 1-RED-BLUE</b> The warning light located on upper rear of the module in the center location shall be dual color red/blue. -----	<b>1.00</b>
<b>WLM90002</b>	<b>LIGHTS REAR WINDOW - 2 WHELEN M9 SUPER LED</b> Two (2) Whelen M9 super LED warning lights with chrome flanges shall be installed on the rear of the module at window level, one (1) on each side. These lights shall operate from a switch on the master control console, labeled "Flashers". -----	<b>1.00</b>
<b>WLCLR1RB</b>	<b>WINDOW LEVEL LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on rear of the module at window level, location 1 shall be dual color red/blue. -----	<b>1.00</b>
<b>WLCLR2RB</b>	<b>WINDOW LEVEL LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on rear of the module at window level, location 2 shall be dual color red/blue. -----	<b>1.00</b>
<b>30-26-3010</b>	<b>LIGHTS, REAR TAIL - WHELEN M6 LED STOP, TURN, BACK-UP</b> Install: (1) pair each of Whelen M6 series LED stop/tail lights, turn lights, and back-up lights with chrome flanges on the rear of the module. -----	<b>1.00</b>
<b>30-26-7002</b>	<b>LIGHT, LICENSE PLATE LED - WHELEN OACOEDCR</b>	<b>1.00</b>



	Install:(1) Whelen OACOEDCR LED license plate light with 45 deg angled chrome-plated bezel on the rear of module, lower left side.	
<b>FILM7T0002</b>	<b>LIGHTS FRONT INTERSECTION - 2 WHELEN M7 LED W/15 DEGREE TILT HOUSING</b> Two (2) Whelen M7 super LED warning lights, with water-proof connectors, shall be mounted in 15 degree tilt housings on the front chassis fenders, one (1) on each side. The lights shall operate from a switch on the master control console labeled "Flashers". NOTE: When vehicle is placed in park, the override switch must be on for intersection light(s) to remain on.	1.00
<b>FILCLR1RB</b>	<b>FRONT INTERSECTION LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on front of the chassis fender in location 1 shall be dual color red/blue.	1.00
<b>FILCLR2RB</b>	<b>FRONT INTERSECTION LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on front of the chassis fender in location 2 shall be dual color red/blue.	1.00
<b>RILCLR1RB</b>	<b>REAR INTERSECTION LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on above the rear wheel well at location 1 shall be dual color red/blue.	1.00
<b>RILCLR2RB</b>	<b>REAR INTERSECTION LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on above the rear wheel well at location 2 shall be dual color red/blue.	1.00
<b>30-27-1102</b>	<b>LIGHTS, ICC / LED CLEARANCE - ON MODULE SIDE - TECNIQ</b> Install: (2) red Tecniq LED (S33-RR00-1) clearance/ICC lights, (1) red on each side at rear of the vehicle, flash with turn signal, per Dwg #3 and #4.	1.00
<b>SWLM90004</b>	<b>LIGHTS SIDE WARNING -4 WHELEN M9 SUPER LED</b> Four (4) Whelen M9 super LED warning lights with chrome flanges shall be installed, two (2) on each side of module exterior per dwg.	1.00
<b>SWLCLR1RB</b>	<b>SIDE WARNING LIGHT LOCATION 1 - RED-BLUE</b> The warning light located on side of the module, in outer location 1 shall be dual color red/blue.	1.00
<b>SWLCLR2RB</b>	<b>SIDE WARNING LIGHT LOCATION 2 - RED-BLUE</b> The warning light located on side of the module, in outer location 2 shall be dual color red/blue.	1.00
<b>SWLCLR3RB</b>	<b>SIDE WARNING LIGHT LOCATION 3 - RED-BLUE</b> The warning light located on side of the module, in outer location 3 shall be dual color red/blue.	1.00
<b>SWLCLR4RB</b>	<b>SIDE WARNING LIGHT LOCATION 4 - RED-BLUE</b> The warning light located on side of the module, in outer location 4 shall be dual color red/blue.	1.00
<b>SSM90004</b>	<b>LIGHTS SIDE SCENE - 4 WHELEN M9 LED</b>	1.00



Four (4) Whelen M9 24 Diode LED scene lights with chrome flanges shall be installed, two (2) each module side. These lights shall operate from switches on the master control console labeled "Left Scene Light" and "Right Scene Light".

-----

### **Braun - Module Body Construction**

<b>Item Number</b>	<b>Description</b>	<b>Quantity</b>
39-00-0005	<b>AWS ALUMINUM CERTIFIED WELDERS</b>	1.00
39-10-0003	<b>CONNECTIONS, MODULE</b> Bolt: to the chassis frame rail with (12) 5/8" -11 grade 8 bolts through OEM rubber insulating spacers installed on outriggers at twelve (12) separate locations (six each frame rail), providing noise insulation and easy removal for chassis replacement, mounting bolts to be properly torqued and secured with locktite, system used for fastening the module to the frame to be that approved by the chassis manufacturer.	1.00
40-00-0080	<b>INSULATION - POLYURETHANE SPRAY FOAM</b> The entire underside of the module floor (except for mounting pads), the underside of the outside storage compartments, the wheel wells, and the underside of the curbside step area shall be completely insulated with sprayed on Class I urethane foam for thermal and acoustical insulation. The insulation shall comply with FMVSS #302 flame spread requirements. The underside of the body shall be properly prepared to ensure adhesion before the spray insulation is applied.	1.00
40-00-0079	<b>INSULATION - EXTERIOR PASSAGE AND OSS DOORS AND INTERIOR WALLS AND CEILING</b> The walls, ceiling, passage doors, and outside storage doors shall have foam for thermal and acoustical insulation. The insulation shall comply with FMVSS #302 flame spread requirements.	1.00
39-00-0001	<b>MODULE BODY CONSTRUCTION - SEAMLESS</b> Module: fabricated entirely of parts cut and formed from .125" (minimum) thickness 5052-H32 flat aluminum sheet stock, using CNC machines capable of .010" repeatability. This is the only alloy that may be used for body parts that are welded together. Roll-cage type interior super-structure, aluminum partition and module welded together into a single unit, roof designed with a minimum 1.5" crown to facilitate water run-off. Floor, roof, sides, all exterior doors fabricated from .125" (minimum) thick flat aluminum sheet stock, exterior joints between the roof and side components continuous full seam welded the entire length of the module. All exterior body panel joints continuous full seam welded. No VHB bonding tape or other adhesives used in the construction of the ambulance module.	1.00
39-00-0002	<b>SOLE SOURCE MODULE BODY CONSTRUCTION</b>	1.00

### **Braun - Module Features / Exterior**



Item Number	Description	Quantity
SR00199004	DOMETIC PENGUIN LOW PROFILE ROOFTOP UNIT: Install a Dometic Penguin low profile rooftop 125-volt AC unit with 1500-watt heater. The model # will be 641835CXX1C0 and will be located per dwg. #9. There shall be an aluminum protective cover for the roof top Dometic Unit on the rooftop AC. Painted to match truck (match 8537) The control for the unit will be installed in the primary action area located per dwg. #5.	1.00
SR00199005	CONDENSER - MODULE FRONT, TOP MOUNT: Install a Hoseline TMC2009 condenser on the module roof, condenser is to be located per dwg. #1, #3 and #4.	1.00
SR00199006	KICKPLATE/THRESHOLD, REAR DOORWAY Install rubber bumpers for the flip-up step to rest on when the step is in the raised position. Per dwg. #2.	1.00
SR00199008	Add black floor tile to compartment floors and shelves	1.00
SR00199014	OSS #4C CURBSIDE: Install OSS #4C above the curbside wheel well. 90 degree drop down door with one rubber bumper in center on exterior of compartment door. inside/outside access from squad bench. No cable.	1.00
SR00199016	OUTSIDE STORAGE #1-STREETSIDE FORWARD-OXYGEN STORAGE Oxygen Location- locate cylinder in OSS #1, includes necessary O2 system and OSS #1 compartment changes. O2 storage will be for an "H" tank. There will be backboard/stair chair storage left side of the compartment with a seat belt type strap to secure both backboards and stair chair. Per dwg. #3.	1.00
SR00199017	Black Gatorhyde: Change interior of OSS compartments from grey gatorhyde to black.	1.00
SR00199023	OUTSIDE STORAGE #3-STREETSIDE REAR-TALL DOOR The inside/outside access for this compartment has been deleted. The upper 30" of the compartment is to be 12" deep. The lower portion of the compartment is to be full depth. In the lower right portion of the compartment there is to be drop-in storage with a minimum of 9.5" and no larger than 10" for two (2) SCBA bottles. Per dwg. #3.	1.00
SR00199044	#5 (forward curbside compartment) shall have a 69.50" high x 17.50" wide clear door opening. The compartment shall be split into two (2) compartments. #5A provides inside/outside storage and shall have two (2) adjustable shelves. (Reference the lower front wall cabinet in patient compartment specification for interior dimensions). #5B dimensions, reference exterior model dwg. #4. The compartment door shall be held open with a spring loaded gas cylinder. A locking handle shall be installed on the exterior of the door.	1.00



SR00199047	----- <b>OUTSIDE STORAGE #4 W/OUTSIDE ACCESS ONLY</b> The standard divider in OSS #4 has been deleted and the compartment will have outside access only. Per dwg. #4.	1.00
SR00199063	----- <b>LOCKS POWER - PASSAGE, COMPARTMENTS, KEY FOBS:</b> Install power door locks on module passage doors, and seven (7) OSS compartments including OSS #2A and #4C, use OEM key fobs.	1.00
SR00199071	----- There will be a total of four (4) equipment hooks installed. Two (2) hooks are to be installed in OSS #3 on the upper portion of the back wall of the compartment. Two (2) hooks are to be installed in OSS #4 that will be mounted to the bottom of the shelf. All hooks are to be spaced far enough apart that the turnout coats can be hung side by side. Per dwg. #3 and #4.	1.00
SR00199074	----- <b>SHELF ONE (1) IN OSS #4</b> Install one (1) adjustable shelf in OSS #4.	1.00
SR00199077	----- <b>SHELF TRACK-EXPOSED-OSS #4</b> Install Unistrut 1-1/4" x 3/4", 19 gauge "T" grooved track channel in OSS #4 (Exposed tracks will be welded in place and coated with Gatorhyde material for a cleaner look and no exposed fasteners).	1.00
SR00199086	----- <b>OSS #2A STREETSIDE</b> Install OSS #2A above the streetside rear wheel well. Compartment is to be built per dwg. #3 dimensions. Compartment will have outside access only. Compartment is to be enclosed by a 90 degree drop down door with one rubber bumper in the center on exterior of compartment door. Per dwg. #3. No cable.	1.00
40-00-0009	----- <b>ALUMINUM PARTS - MODULE EXTERIOR</b> All unpainted exterior aluminum parts to be bright dip anodized after fabrication to retain the finish and increase corrosion resistance.	1.00
40-00-0010	----- <b>CORROSION MINIMIZATION - MODULE</b> All module contact with dissimilar metals shall be minimized with the use of nylon screw-hole inserts to provide hinge to door isolation with the module body, polypropylene strip hinge isolation, polyethylene backed rubber tape, ceramic coated stainless steel hinge bolts, and corrosion inhibitor spray.	1.00
40-00-0020	----- <b>DOOR CONSTRUCTION - GASKET PLACEMENT</b> All exterior hinged module doors shall be constructed in an inverted pan-formed design. The pan shall be constructed from .125" thick 5052-H32 flat sheet aluminum. The exterior door skin shall be constructed of .190" thick aluminum and welded to the pan. Door gaskets shall be attached to the interior side of the door skin on the top, bottom and outer edge of the door. The gasket on the hinge side of the door will be attached to the door frame.	1.00
40-00-0060	----- <b>EXTERIOR COMPARTMENTS - SWEEP-OUT</b>	1.00



Exterior module compartments: a sweep-out design to aid in facilitation of the purchaser's routine care and cleaning of the vehicle. All exterior compartment floors, with the exception of the front ALS compartment to be constructed to be flush with the bottom door frame.

40-00-0030	<p><b>EXTERIOR COMPARTMENTS DESIGN</b></p> <p>All exterior compartments shall be vented and include: sound absorbing slip resistant polyurethane material sprayed on the inside of all compartments and compartment shelving, slide out trays and closeouts, baffled seep holes provided to prevent water from splashing or seeping into the exterior compartments, full-length, two-way adjustable, stainless steel hinges on all exterior compartment doors with 3/16" stainless steel hinge pins, compartment doors installed, flush with the module body, when double doors are provided, each door to have exterior handle, but only the forward door lockable, rearward door is secured when forward door is locked), all exterior compartments and passage doors keyed alike, lockable Eberhard "free-floating" type chrome plated handles with rotary locks. Gasket installed under each handle to protect the paint; drip rails installed above all exterior compartment doors.</p>	1.00
40-00-0050	<p><b>EXTERIOR COMPARTMENTS, VENTING</b></p> <p>(9) square inches (minimum) of venting inside #1, #2, #3, &amp; #4 exterior storage compartments to provide for easier closure of the compartment doors.</p>	1.00
40-00-0055	<p><b>EXTERIOR COMPARTMENTS, VENTING - OXYGEN STORAGE</b></p> <p>(9) square inches (minimum) of venting provided in the exterior oxygen storage compartment, to dissipate any leaking oxygen gas.</p>	1.00
40-00-0070	<p><b>HANDLES, EBERHARD - CHROME FREE FLOATING TYPE</b></p> <p>Install: Eberhard #EMC-1-2110 chrome "free-floating" handles on each exterior module door, large enough to accommodate a gloved hand.</p>	1.00
40-10-0072	<p><b>LOWERED MODULE SIDES</b></p> <p>Module sides to be as low as possible and still comply with KKK-1822-F ramp break over angle.</p>	1.00
40-10-0321	<p><b>STEPWELL, CURBSIDE DOORWAY - MID STEP AREA</b></p> <p>Install: aluminum diamond plate step well and mid-level step in curbside doorway threshold area.</p>	1.00
40-00-0091	<p><b>THRESHOLD, STAINLESS STEEL - ALL OSS STORAGE COMPARTMENTS</b></p> <p>Each exterior storage compartment with a hinged door: stainless steel lower threshold at the door opening to protect the paint.</p>	1.00
40-00-0085	<p><b>COATING, CERAMIC THERMAL</b></p> <p>Apply: Temp-Coat ceramic thermal barrier coating to the interior of the module roof after the spray foam application, to meet or exceed the manufacturer's recommended thickness.</p>	1.00
40-10-0340	<p><b>STONE GUARDS, MOD FRNT -ANODIZED DIAMOND PLATE</b></p> <p>Install: anodized aluminum diamond plate stone guards on module front, (1) each side.</p>	1.00
40-10-0066	<p><b>DOOR SLIDING - MODULE CURBSIDE PASSAGE</b></p> <p>Install EZ Glide curb door.</p>	1.00





40-10-0088	<b>DOORS - REAR PASSAGE</b> Patient compartment rear door opening: doors flush without a protruding flange or lip, right rear passage door lockable, chrome exterior handle, left rear door non-locking, chrome exterior handle, all handles installed with a gasket, hinge full length stainless steel with a 3/16" stainless steel hinge pin, two-way adjustable, each rear door two-point slam action automotive type rotary latching system to the body, right rear door lock to the body at the top and bottom, not to left rear door, doors .218" stainless steel door latch activator rods with clevis adjusters, doors lockable from inside and outside, shut on molded, air-core, automotive type door seals to prevent water from leaking into vehicle interior.	1.00
40-10-0505	<b>WINDOWS, PASSAGE DOOR - (CURB SLIDING, REAR FIXED)</b> Curbside passage door (sliding) window with removable screen, rear passage doors w/ non-openable window, windows 69% dark tint, secured with black oxide coated fasteners, open doors not to block warning lights.	1.00
40-10-0103	<b>FENDERETTES - POLISHED ALUMINUM</b> Install: Polished aluminum fenderettes around the rear wheel well openings.	1.00
40-10-0119	<b>HOLD-OPEN - REAR DOORS - GRABBERS</b> Install: door grabbers (1 pair) with hard rubber inserts on rear doors.	1.00
40-10-0204	<b>MUD FLAPS, REAR - BLACK RUBBER FIBERGLASS REINFORCED - THREE COLOR</b> Install black rubber, fiberglass reinforced mud flaps with a minimum 1/4" thickness bolted to underside of module behind rear wheels, to provide adequate coverage of ear dual wheels of the chassis, mud flaps to be (3) color with the Manufacturers Logo.	1.00
40-10-0266	<b>REAR STEP/BUMPER -FLIP-UP CENTER SECTION - STAR PUNCHED AND ANODIZED</b> Affix: rear bumper to chassis frame, constructed with a hinged center section, (2) steel braces to secure step to chassis frame, outer 17" on each end of bumper constructed from heavy gauge stamped polished stainless steel bumper parts, to provide smooth rounded corners, step constructed of star punched .125" thick aluminum diamond plate, (2) rear LED step illumination lights provided. All diamond plate surfaces to be anodized; strip of black PVC installed on face of step.	1.00
40-10-0381	<b>TOW HOOKS, MODULE REAR</b> Secure: fasten (2) tow hooks in rear step area to rear step braces.	1.00
40-10-0283	<b>RUB RAILS, ANODIZED ALUMINUM, "C" CHANNEL</b> Install: anodized aluminum "C" channel rub rails on lower sides of body below outside compartment sill areas, rub rails to be offset 3/16" from body.	1.00
40-00-0019	<b>DOOR SKINS, OUTSIDE STORAGE COMPARTMENTS - DIAMOND PLATE INTERIOR SKINS</b> Interior door skins for all outside storage compartments constructed of .063" thick aluminum diamond plate.	1.00
OS2XL1STD	<b>OSS #2 - STREETSIDE CENTER</b> OSS #2 streetside center, hinged double doors with spring-loaded gas cylinders, handles installed on the exterior of each door, forward door with locking handle.	1.00
OS2XL1OP6	<b>OSS #2 - OPEN STORAGE COMPARTMENT</b> OSS #2 streetside center.	1.00



OS3XL1STD	OSS #3 - STREETSIDE REAR - TALL DOOR OSS #3 streetside rear, hinged door with spring-loaded gas cylinder, locking handle installed on the exterior of the door. -----	1.00
-----------	---	------

#### **Braun - Module Interior / Patient Compartment**

<b>Item Number</b>	<b>Description</b>	<b>Quantity</b>
SR00202108	Countertop color is Galaxy Mist -----	1.00
SR00198998	ATTN SEAT-EVS HiBAC, INTEGRAL CHILD, SWIVEL BASE CN8 COMPLIANT A rear facing EVS HiBAC attendant seat shall be installed at the head of the patient cot. This seat shall be equipped with a sliding swivel base and incorporate an integral child safety restraint system. The seat shall be KKK-A-1822F Change Notice 8 compliant with V4 harness style shoulder/seat belt and conform to all applicable FMVSS and SAE J3026 requirements. Documentation from a certified independent testing facility shall be required stating the seat has passed SAE J3026 requirements and tested in accordance with SAE J2917, Occupant Restraint and Equipment Mounting Integrity-Frontal Impact System-Level Ambulance Patient Compartment and SAE J2956, Occupant Restraint and Equipment Mounting Integrity-Side Impact System-Level Ambulance Patient Compartment. The seat shall be padded and covered with color coordinating, cushioned vinyl. -----	1.00
SR00199002	ATTENDANT SEAT-CENTERED WITH COT Attendant seat shall be centered with cot per dwg. #9. -----	1.00
SR00199010	Add Stryker Cot wheel guide mounted on SS wall (See Type II configuration) -----	1.00
SR00199015	Left wall cabinet #3 has been modified (length) due to the additional cabinet that is being installed above the deleted CPR seat. Cabinet is to be built per dwg. #5 dimensions. Cabinet is to have a fixed center divider with one (1) adjustable shelf each side of the divider. Cabinet is to be enclosed by a set of sliding polycarbonate doors. Per dwg. #5. -----	1.00
SR00199021	Install 48" stainless steel grab rail over the streetside area. Install 96" stainless grab rail over the cot. -----	1.00
SR00199022	Left wall cabinet #4 will be inside access only and will be built per dwg. #5 dimensions. Cabinet will have one (1) adjustable shelf. Cabinet will be enclosed by a set of sliding polycarbonate doors. Per dwg. #5. -----	1.00
SR00199024	Left wall cabinet #1 has been modified (width) due to the extended primary action area and the deleted CPR seat. Cabinet is to be built per dwg. #5 dimensions. Cabinet is to have a fixed center divider with one (1) adjustable shelf each side of	1.00



	the divider. Cabinet is to be enclosed by a set of sliding polycarbonate doors. Per dwg. #5.	
SR00199026	SHARPS AND TRASH CONTAINERS-ACCESS THRU SQUAD BENCH LID Install a spacer for the sharps and waste containers in the squad bench.	1.00
SR00199031	A 16.00" x 17.75" dry erase board shall be installed on the curbside wall IATS, per dwg. #6. Two (2) dry erase markers and one (1) eraser shall be shipped loose with the completed ambulance.	1.00
SR00199035	RADIO SPEAKERS, CEILING (OEM RADIO & ACP FADER CONTROL) Two (2) radio speakers shall be installed in the ceiling located per dwg. #9. The fader control for the rear speakers shall be provided through the OEM radio and a fader control located in the ACP.	1.00
SR00199039	Install left wall cabinet #2 per dwg. #5 dimensions and location. Cabinet will have a fixed center divider with one (1) adjustable shelf each side of the divider. Cabinet is to be enclosed by a set of sliding polycarbonate doors. Per dwg. #5.	1.00
SR00199041	The lower front interior wall shall have two (2) cabinets with two (2) adjustable shelves on Unistrut adjustable brackets. The lower shelf shall serve as the divider for the cabinets. I/O access / the upper compartment shall be enclosed by a black cargo net over the opening with buckles at the bottom. The lower #3 cabinet shall be enclosed by a black cargo net over the opening with buckles at the bottom. Per dwg. #7.	1.00
SR00199045	All seat belts are to be red.	1.00
SR00199049	PARAMEDICS DESIGN PD7 ORGANIZER Install a Paramedics Design PD7 organizer at the rear end of the squad bench seating area. Located per dwg. #6 and #8.	1.00
SR00199050	A total of six (6) assist handles shall be provided: two (2) 1-1/4" diameter stainless steel "V" handles, one (1) on each rear passage door; and four (4) stainless steel assist handles, two (2) handles at the rear passage doorway, one (1) at the curbside doorway and one (1) on the curbside sliding door.	1.00
SR00199051	SQUAD BENCH TOP SPLIT-WITH SHARPS/TRASH ACCESS Squad bench top and cushions shall be covered with color coordinated vinyl upholstery material and sewn with seams only at the vertical corners. The squad bench lid is to be split per dwg. #6. The squad bench has been raised due to the OSS #4C compartment.	1.00



SR00199057	OXYGEN OUTLET (1) RIGHT WALL - OHIO MED - HEAD END OF SEATING AREA: One (1) Ohio Medical flush mounted; quick release wall outlet shall be installed in the right wall above the head end of the curbside seating area, 1.5" below standard location. Per dwg #6	1.00
SR00199060	STAINLESS STEEL WALL PROTECTION-INTERIOR STREETSIDE The stainless steel on the streetside interior of the module has been deleted. Flooring is to be 12" high per dwg. #5.	1.00
SR00199061	SEATING-SQUAD BENCH EVS Install two (2) EVS V4 harnessed seated positions. Retractors will be installed for second patient transport. Squad bench will have access to the OSS #4C compartment. Per dwg. #6.	1.00
SR00199062	Install three (3) Perko #1309 IV hooks and straps IPOS. Two (2) located per dwg. #5 and one (1) located per dwg. #6.	1.00
SR00199070	RECESSED MEDVAULT Install a recessed MedVault in the primary action area located per dwg. #5. MedVault is to be WiFi capable. MedVault is to be wired hot at all times. The fuse is to be pulled from the MedVault after it has been installed and then will be reinstalled at final inspection. Per dwg. #5. Does not include cloud agreement. The customer must purchase cloud agreement before we can order the Medvault.	1.00
SR00199072	"D" Cylinder O2 Storage "D" Cylinder O2 storage selected in configuration shall be mounted in the walk-thru on the side wall of the ALS stack facing the PDQ.	1.00
SR00199083	The primary action area has been extended due to the deletion of the CPR seat and the secondary action area. Primary action area is to be built per dwg. #5 dimensions.	1.00
50-51-1001	<b>CABINET CONSTRUCTION - INTERIOR - ALUMINUM</b> All interior cabinets shall be constructed of .090" thick welded aluminum.	1.00
50-51-1014	<b>CATCH, MAGNETIC - ADHESIVE BACK FOR INTERIOR DOOR(S) OVER 36 INCHES</b> All interior doors that are over 36" inches tall with a latch on the top of the door shall have an adhesive back magnetic catch installed on the bottom of the door.	1.00
50-60-0220	<b>EMBLEMS / SIGNS - REAR PATIENT COMPARTMENT</b> (2) "No Smoking / Oxygen Equipped / Fasten Seat Belts" signs: (1) sign installed in the cab, (1) above the oxygen outlets in the patient compartment street side cabinet.	1.00
50-60-0300	<b>FLOOR CONSTRUCTION- PATIENT COMPARTMENT, NON-WOOD COMPOSITE</b> Sub-floor in the patient compartment: constructed of .125" thick aluminum over .125" and .190" thick reinforcing hat sections and mounting laterals, aluminum sub-floor covered with a 3/4" non-wood composite material, all corner molding, edging	1.00



	and trim anodized aluminum or stainless steel and sealed to prevent fluids from seeping under the cabinets.	
<b>50-60-0301</b>	<b>FLOORING - COVE</b> Patient compartment floor radius: coved with pre-formed floor coving material, installed behind the vinyl floor covering, along both the street side and curbside walls.	1.00
<b>50-60-0391</b>	<b>HEADLINER - REAR PATIENT COMPARTMENT</b> Headliner in the patient compartment shall be one-piece, seamless, .090 thick aluminum finished with sprayed-on multi-use polychromatic coating.	1.00
<b>50-51-1013</b>	<b>HOLD OPENS FOR INTERIOR DOORS</b> All interior cabinets with doors less than 6" tall shall have friction hinges as hold opens for door(s). Doors 6" and taller shall be designed using gas shocks as hold opens for the door(s).	1.00
<b>50-60-0660</b>	<b>PADDED EDGING PROTECTION</b> Install: padded corner edging where necessary on exposed corners and edges in the patient compartment for patient and attendant protection.	1.00
<b>50-00-0202</b>	<b>ROUNDED INTERIOR CORNERS</b> Interior vertical edges: rounded/padded corners in the following locations: forward and aft edges of the CPR seat, the wall at the aft end of the squad bench, the partition opening cabinet edges and the upper front wall cabinet.	1.00
<b>50-51-1011</b>	<b>RECESSED ADJUSTABLE SHELF TRACK - CABINETS</b> Install recessed adjustable shelf track in cabinets.	1.00
<b>50-51-5001</b>	<b>UPHOLSTERY - PATRIOT PLUS CHARCOAL #8605</b> All cushions, head pads and seating surfaces shall be covered with Patriot Plus Charcoal #8605	1.00
<b>50-60-0661</b>	<b>INTERIOR MODULE PADS</b> Vinyl upholstered, foam cushioned head/back pads shall be installed as follows: the lower edge of the upper front wall cabinet (above the partition doorway or window), above the rear doors, above the side door, and on the street side wall behind and on each side of the CPR seat. The pads shall be covered with a flame-retardant color coordinated vinyl upholstery material.	1.00
<b>50-51-6003</b>	<b>LONPLATE II, NON-SLIP EMBOSSED SM. GRID - GUNMETAL #424</b> The floor in the patient compartment shall be covered with Lonseal brand "Lonplate II" non-slip; small grid (embossed) Gunmetal #424.	1.00
<b>50-51-2002</b>	<b>CABINET DOORS - CLEAR POLYCARBONATE</b> All cabinet doors shall be clear polycarbonate material / installed in aluminum track lined with PPL inserts / An edge mounted aluminum handle shall be installed on each sliding cabinet door.	1.00
<b>50-51-3001</b>	<b>CABINETS/ WALLS - POLYCHROMATIC COATING - MARBLE STONE</b>	1.00



	Headliner, walls, cabinet faces, and cabinet interiors MultiSpec color to be Marble Stone	
IS-CNT-ACR	<b>COUNTER TOP, SOLID ACRYLIC</b> Install: solid acrylic countertop with 1/2" lip on the primary action area.	1.00
50-01-0408	<b>LATCHES, CABINET, CN10 COMPLIANT AS APPLICABLE - INCLUDING RADIO CABINET</b> The ACP (attendant control panel) door, the PDQ (power distribution quarters) door, and the radio cabinet door shall be secured with chrome locking lever latches/ all remaining interior hinged cabinet doors with center squeeze latches/all interior drawers with locking flush pull latches.	1.00
50-10-0229	<b>LEFT WALL - ATTENDANT CONTROL PANEL - WITH FLAT AREA</b> A control screen shall be mounted on a hinged access panel and secured with two (2) latches. The panel will be located to the immediate right of the attendant's seat. The forward portion of the panel will contain a flat area that may be used for future radio mounting, etc.	1.00
IS5XL1OP1	<b>PULL-OUT DRAWER WITH HINGED ACRYLIC WRITING SURFACE AND LOCKING STAINLESS STEEL FLUSH PULL LATCH. RECESSED SUCTION BELOW DRAWER</b> Left lower wall: (1) drawer (#5) aisle facing, primary action area, under the attendant control panel, hinged acrylic writing surface, locking stainless steel flush pull latch. A recessed SSCOR suction canister shall be located below the drawer. An SSCOR suction system with a 12 VDC electric vacuum pump: recessed into the street side lower interior wall near the attendant seat, pump shall be mounted in the standard OSS #2, pump exhaust shall be vented to the exterior of the vehicle. (must use SSCOR pump and tubing)	1.00
50-60-0018	<b>ASPIRATOR / SUCTION - SSCOR - WITH ELECTRIC PUMP - RECESSED</b> An SSCOR suction system shall be recessed into the street side lower interior wall near the attendant's seat. The 12 VDC SSCOR electric vacuum pump to be installed in an exterior compartment per the location on the drawing (must use SSCOR pump and tubing).	1.00
IC1XL1OP3	<b>CABINET #1 OPTION REMOVED</b> Cabinet #1 will be removed/ omitted	1.00
50-50-0541	<b>HOLD OPENS - SQUAD BENCH LID - GAS CYLINDERS</b> Gas cylinder hold-open(s) shall be provided and installed to hold lid in the open and closed position.	1.00
50-60-0709	<b>SHARPS AND TRASH CONTAINERS - ACCESS THRU SQUAD BENCH LID</b> A sharps container and a trash container installed in the forward end of the squad bench base, containers accessed through the squad bench lid covered with a 3/8" thick clear acrylic hinged lid with a biohazard warning label.	1.00
50-60-0718	<b>SQUAD BENCH FACE - VINYL FLOORING MATERIAL</b> The face of the squad bench shall be covered with vinyl flooring material.	1.00
SQ-BN-BASE	<b>SQUAD BENCH BASE W/STORAGE</b> A storage area shall be provided in the squad bench base. The squad bench base shall be constructed of .090" thick aluminum for maximum storage capacity and minimum weight. The interior of the squad bench shall be sprayed with sound absorbing	1.00



	polyurethane material.	
IF3PDQ	<p><b>CABINET - PDQ</b></p> <p>The Power Distribution Quarters (PDQ) shall hold electrical components, (i.e., power distribution nodes, circuit breakers, etc.), hinged door with (2) chrome locking lever latches, located on the partition wall behind the attendant seat.</p>	1.00
IF1XL1C4	<p><b>CABINET - FRONT WALL, UPPER #1 - HINGED ALUMINUM DOOR W/INSERT</b></p> <p>The front wall interior cabinet #1, flip up hinged aluminum door with polycarbonate insert and gas shock hold-open(s), latch, (1) adjustable shelf.</p>	1.00
IF1XL1OP4	<p><b>CABINET WITH HINGED ALUMINUM DOOR WITH POLYCARBONATE INSERT AND LATCH WITH (1) ADJUSTABLE SHELF</b></p> <p>Install cabinet with hinged aluminum door with polycarbonate insert and gas shock hold-open(s) in the upper front wall.</p>	1.00
IF3XL1OP1	<p><b>CABINET - VENTED RADIO CABINET PDQ ABOVE</b></p> <p>Power Distribution Quarters (PDQ) compartment and a vented radio compartment below the PDQ, lower front wall, left.</p>	1.00
IF3XL1RAD	<p><b>CABINET - FRONT WALL, LOWER BELOW PDQ (SINGLE VENTED DOOR)</b></p> <p>A radio cabinet with a vented, hinged aluminum door, secured by a chrome locking lever latch, located on the front lower left wall, door to open towards rear of the module.</p>	1.00
IF4XL1OP1	<p><b>PASS-THROUGH WINDOW OPEN TO THE CAB</b></p> <p>Window opening, pass-through from cab to module.</p>	1.00
50-20-0507	<p><b>PASS THROUGH - CAB TO MODULE, WINDOW OPENING</b></p> <p>A window opening: provided in the rear of the cab to accommodate pass-through communications to the patient compartment, bellows provided to connect the cab to the module.</p>	1.00
HVAC_HSL_STD_01	<p><b>HVAC - THE EVAPORATOR IS TIED-IN TO THE OEM AIR CONDITIONING SYSTEM, COOLING THE AIR OF THE PATIENT COMPARTMENT THROUGH THE VENTS (STANDARD SETUP)</b></p> <p>The air conditioning unit shall be tie-in to the OEM air conditioning system, cooling the air of the patient compartment through the outlets. The evaporator unit shall have a capacity of 580 CFM and cooling capacity of 30,000 BTU. The evaporator shall be installed in the patient compartment, in the upper front wall. It shall be accessible by removing the HVAC faceplate. Adjustable vents with manual closures are installed within the HVAC faceplate. The patient compartment HVAC system shall be controlled by the driver or the patient compartment attendant via the multiplex located in the front console or the rear switch panel. The patient compartment temperature shall be monitored by a thermostat incorporated in the multiplexing electrical system. Additional to the three (3) preprogrammed speeds, an automatic mode shall be able to decide between heating, cooling and fan speed in function of the set temperature versus the patient compartment temperature. In order to achieve maximum efficiency and optimization of this system, the fans' speed shall be optimized via Pulse Width Modulation (PWM) to allow the heating and cooling system to run at its most effective speed. Adequate room for hose connections and hose lines shall be provided when installing HVAC components. The hoses shall be</p>	1.00



	protected and insulated to optimize performance and longevity. Meets or exceeds AMD-012 testing.	
50-60-0730	<b>DOOR PANELS - MODULE PASSAGE DOORS - FULL LENGTH ALUMINUM - W/ACCESS PANELS</b> Interior rear and curbside passage door panels to be full length aluminum, Multi-Spec sprayed to match interior color and contain removable latch access panel per dwg. # 6 & # 8. (Total 3).	1.00
50-60-0256	<b>EXHAUST VENTILATOR, 3-SPEED - MULTIPLEX ELECTRIC SYSTEM</b> Install: three-speed, 250 CFM (minimum) exhaust fan in the street side cabinet in the patient compartment, fan pulse width modulated from a switch on the attendant control panel control screen, exhaust system to have a louvered grille inside and a chrome vent outside, system vent through the side of the vehicle.	1.00
50-60-0322	<b>GLOVE DISPENSER - (3) BOX - ABOVE ENTRY DOOR - CURBSIDE (ABS)</b> A three (3) - box glove dispenser unit, with a clear acrylic hinged access panel with three (3) cut-outs, shall be provided above the curbside entry door. A 1/4" turn latch will be installed on the face of the glove box access panel.	1.00
50-60-0640	<b>OXYGEN SYSTEM, ELECTRIC - MULTIPLEX ELECTRIC SYSTEM</b> A 12 VDC controlled electric O2 system operated through the electrical system shall be provided and installed.	1.00
50-60-1601	<b>OXYGEN OUTLET (1) LEFT WALL - OHIO MED - ACTION AREA</b> One (1) Ohio Medical flush mounted; quick release wall outlet shall be installed in the forward street side cabinet action area. Per dwg #5	1.00
50-60-0629	<b>FLOW METER, OXYGEN - THORPE STYLE</b> One (1) Thorpe style oxygen flow meter (15LPM) shipped loose with the completed vehicle.	1.00
50-60-0591	<b>NET, SQUAD BENCH - CURBSIDE INTERIOR (RED)</b> Net, Squad Bench - red shall be installed at the head of the squad bench.	1.00
50-60-0277	<b>OXYGEN - ZICO QR-D-2 PORTABLE OXYGEN STORAGE BRACKET ONE (1) IN PASS THRU</b> One (1) Zico QR-D-2 storage bracket shall be installed in the pass thru for one (1) "D", Jumbo "D", or steel "D" oxygen cylinder.	1.00

#### **Braun - Optional Patient Compartment Items**

<b>Item Number</b>	<b>Description</b>	<b>Quantity</b>
SR00199012	<b>Stryker Powerload</b> Clarification: The cot mount is side mount. Match 9143-44	1.00
50-62-0430	<b>COT FASTENER - STRYKER POWER LOAD SYSTEM - SIDE POSITION CN8 COMPLIANT</b> Install : Stryker Power Load Cot System (side position). Install transfer relay and breaker to allow system to charge only when the shoreline is plugged in or when the system is active.	1.00
50-62-0122	<b>COT - STRYKER #6506 POWER PRO XT (W/COMPATIBILITY KIT)</b>	1.00





Provide a Stryker #6506 Power PRO XT cot, (this cot to include the powerload compatibility kit so it can be used with powerload system)  
-----

### Braun - Paint / Graphics

Item Number	Description	Quantity
SR00199048	<b>CAB PAINT</b> Cab is to be painted per the attached layout. Paint codes are as follows: Charcoal Metallic- Sherwin Williams Ultra 7000-108681493. Dark Red- Axalta L0176CT -----	1.00
SR00199075	<b>GRAPHICS</b> Graphics are to be per the attached layout. Unit numbers shall be TBD. -----	1.00
SR00199076	<b>MODULE PAINT</b> Module is to be painted per the attached layout. Paint codes are as follows: Dark Red Axalta L0176CT. -----	1.00
60-01-0001	<b>PAINT PROCEDURE</b> All non-anodized aluminum module body surfaces: completely chemically steam cleaned, filled with premium body filler as needed, sanded smooth and primed with an epoxy primer and then primed again with a high solid primer, cured primer surfacer shall be DA sanded with 320 grit and cleaned. A high solid primer shall then be applied, where needed, as a sealer. -----	1.00
60-01-0005	<b>STANDARDS AND SPECIFICATIONS FOR VEHICLE PAINT APPEARANCE</b> -----	1.00
60-01-0017	<b>BUFF PAINT - STANDARD CAB TYPE I</b> The paint on the cab shall be buffed to a high shine using a recommended paint buff system. -----	1.00
60-01-0004	<b>BUFFING, PAINT - MODULE</b> The paint on the module sides shall be buffed to a high shine using a recommended paint buff system. -----	1.00
60-20-0301	<b>CHEVRON STRIPING - FULL COVERAGE</b> Chevron striping 6" wide inverted "V" shall be installed on the complete rear of the module. -----	1.00
60-30-0200	<b>REFLECTIVE - DOOR REFLECTIVITY</b> Install reflective material (25" x 2.5" red/silver chevron style), on the lower interior stainless steel panel of each rear door and hinged side door. NOTE: If a sliding side door is provided, install a 1.50" x 40.00" white reflective stripe on the rear facing edge. -----	1.00

### Braun - Vehicle Manuals



Item Number	Description	Quantity
80-20-0001	<b>VEHICLE MANUALS (1) PACKAGE SET</b> One (1) Delivery Manual Package shall be supplied with the vehicle and shall include the following items: Ambulance manufacturer parts, service, and operation manuals, OEM chassis owner's guide, complete 12 VDC and 125 VAC wiring schematics for all included standard and optional systems, Multiplex Electrical system programming - electronic media -----	1.00
90-10-0007	<b>STATEMENT OF LIMITED WARRANTY NEW AMBULANCES</b> -----	1.00